

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P684161

Luminaire Tested: **LX6C25D010 EX6C259050 6LBMH**

Issue Date: 2/15/2022



Test Information

Test Method: LM-79-08
Report Number: P684161
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P203254)
Test Lab: INNOVATION CENTER
Issue Date: 2/15/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX6C25D010 EX6C259050 6LBMH
Description: 6 INCH 2500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 5000K, 90CRI LEDS
AND 6LBM TRIM WITH H FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1938.0 lumens
Efficiency: N/A
Efficacy: 61.5 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.93
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 31.5
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P684161

CATALOG NUMBER: LX6C25D010 EX6C259050 6LBMH

Luminous Intensity Polar Plot





TEST NUMBER: P684161

CATALOG NUMBER: LX6C25D010 EX6C259050 6LBMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	92	92	92	92
2	107	102	97	93	105	100	96	92	97	93	90	94	91	88	91	89	87	85	85	85	85
3	101	94	88	84	99	92	88	84	90	86	82	87	84	81	85	82	80	78	78	78	78
4	95	87	81	76	93	86	80	76	84	79	75	82	78	74	80	76	73	72	72	72	72
5	90	81	75	70	88	80	74	70	78	73	69	76	72	68	75	71	68	66	66	66	66
6	85	75	69	64	83	75	69	64	73	68	64	72	67	63	70	66	63	61	61	61	61
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57	57	57	57
8	76	66	60	55	75	65	59	55	64	59	55	63	58	55	62	58	54	53	53	53	53
9	72	62	56	51	71	61	55	51	60	55	51	60	55	51	59	54	51	49	49	49	49
10	69	58	52	48	68	58	52	48	57	52	48	56	51	48	55	51	48	46	46	46	46

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	105145
5°	103257
10°	97983
15°	91885
20°	85571
25°	78845
30°	65694
35°	46304
40°	29512
45°	17599
50°	10388
55°	6604
60°	4550
65°	3230
70°	2228
75°	1758
80°	852
85°	0



TEST NUMBER: P684161

CATALOG NUMBER: LX6C25D010 EX6C259050 6LBMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	175.4	9.0
10°-20°	453.7	23.4
20°-30°	587.8	30.3
30°-40°	436.4	22.5
40°-50°	184.2	9.5
50°-60°	65.4	3.4
60°-70°	25.2	1.3
70°-80°	8.7	0.5
80°-90°	1.1	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1216.8	62.8
0°-40°	1653.3	85.3
0°-60°	1902.9	98.2
0°-90°	1938.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1938.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1918	
5°	1876	175
15°	1619	454
25°	1304	588
35°	692	436
45°	227	184
55°	69	65
65°	25	25
75°	8	9
85°	0	1
90°	0	



TEST NUMBER: P684161

CATALOG NUMBER: LX6C25D010 EX6C259050 6LBMH

CANDELA DISTRIBUTION (FULL):

	0°
0°	1918.0
2.5°	1912.4
5°	1876.4
7.5°	1823.8
10°	1760.2
12.5°	1691.0
15°	1619.0
17.5°	1538.8
20°	1466.8
22.5°	1392.1
25°	1303.5
27.5°	1181.7
30°	1037.8
32.5°	869.0
35°	691.9
37.5°	542.5
40°	412.4
42.5°	307.2
45°	227.0
47.5°	166.0
50°	121.8
52.5°	91.3
55°	69.1
57.5°	52.5
60°	41.5
62.5°	30.5
65°	24.9
67.5°	19.3
70°	13.9
72.5°	11.0
75°	8.3
77.5°	5.6
80°	2.7
82.5°	2.7
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)