

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P685028

Luminaire Tested: **LX6C45D010 EX6459040 6LBNLI**

Issue Date: 2/14/2022



Test Information

Test Method: LM-79-08
Report Number: P685028
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205310)
Test Lab: INNOVATION CENTER
Issue Date: 2/14/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX6C45D010 EX6459040 6LBNLI
Description: 6 INCH 4500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, 90CRI LEDS
AND 6LBN TRIM WITH LI FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3845.1 lumens
Efficiency: N/A
Efficacy: 77.5 lumens/watt
Spacing Criteria (0/90/45): 0.53 / 0.53 / 0.58
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 49.6
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P685028

CATALOG NUMBER: LX6C45D010 EX6459040 6LBNLI

Luminous Intensity Polar Plot





TEST NUMBER: P685028

CATALOG NUMBER: LX6C45D010 EX6459040 6LBNLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	114	112	109	107	112	109	107	106	105	104	102	102	101	99	98	97	96	95			95
2	109	105	101	98	107	103	100	97	100	97	95	97	95	93	94	93	91	89			89
3	105	99	94	91	103	97	93	90	95	91	89	93	90	87	90	88	86	85			85
4	100	93	88	85	98	92	88	84	90	86	83	88	85	82	86	84	81	80			80
5	96	88	83	79	94	87	83	79	86	82	78	84	81	78	83	80	77	76			76
6	92	84	79	75	90	83	78	75	82	77	74	80	76	74	79	76	73	72			72
7	88	80	74	71	87	79	74	71	78	73	70	77	73	70	76	72	69	68			68
8	84	76	71	67	83	75	70	67	74	70	67	73	69	66	73	69	66	65			65
9	81	73	67	64	80	72	67	64	71	67	63	70	66	63	70	66	63	62			62
10	78	69	64	61	77	69	64	61	68	64	61	67	63	60	67	63	60	59			59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	479907
5°	448794
10°	366025
15°	269349
20°	185650
25°	137827
30°	103529
35°	64561
40°	31337
45°	10753
50°	1407
55°	1070
60°	614
65°	726
70°	898
75°	0
80°	0
85°	0



TEST NUMBER: P685028

CATALOG NUMBER: LX6C45D010 EX6459040 6LBNLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	727.8	18.9
10°-20°	1306.4	34.0
20°-30°	1056.3	27.5
30°-40°	608.5	15.8
40°-50°	128.6	3.3
50°-60°	11.1	0.3
60°-70°	5.6	0.1
70°-80°	0.7	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3090.5	80.4
0°-40°	3699.0	96.2
0°-60°	3838.8	99.8
0°-90°	3845.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3845.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	8754	
5°	8156	728
15°	4746	1306
25°	2279	1056
35°	965	608
45°	139	129
55°	11	11
65°	6	6
75°	0	1
85°	0	0
90°	0	



TEST NUMBER: P685028

CATALOG NUMBER: LX6C45D010 EX6459040 6LBNLI

CANDELA DISTRIBUTION (FULL):

0°	
0°	8754.2
2.5°	8649.0
5°	8155.5
7.5°	7445.8
10°	6575.4
12.5°	5682.8
15°	4745.9
17.5°	3842.1
20°	3182.3
22.5°	2677.8
25°	2278.6
27.5°	1940.5
30°	1635.5
32.5°	1297.4
35°	964.7
37.5°	670.8
40°	437.9
42.5°	266.2
45°	138.7
47.5°	55.4
50°	16.5
52.5°	16.5
55°	11.2
57.5°	11.2
60°	5.6
62.5°	5.6
65°	5.6
67.5°	5.6
70°	5.6
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)