

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P710915

Luminaire Tested: **LD6C05D010 EU6059027 6LBHYH**

Issue Date: 10/18/2023



**Test Information**

Test Method: LM-79-08  
Report Number: P710915  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-7)  
Test Lab: INNOVATION CENTER  
Issue Date: 10/18/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD6C05D010 EU6059027 6LBHYH  
Description: 6 INCH 500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 2700K, 90CRI LEDS AND 6LCHYP TRIM WITH MW FINISH  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 497.7 lumens  
Efficiency: N/A  
Efficacy: 69.1 lumens/watt  
Spacing Criteria (0/90/45): 0.59 / 0.59 / 0.59  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 7.2  
Input Voltage (V):  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P710915

CATALOG NUMBER: LD6C05D010 EU6059027 6LBHYH

### Luminous Intensity Polar Plot





TEST NUMBER: P710915

CATALOG NUMBER: LD6C05D010 EU6059027 6LBHYH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	115	112	110	108	112	110	108	107	106	105	103	103	101	100	99	98	98	96	96	96	96
2	110	106	103	100	108	105	102	99	102	99	97	99	97	95	96	95	93	92	92	92	92
3	106	101	97	94	105	100	96	93	97	94	92	95	93	91	93	91	89	88	88	88	88
4	103	97	92	89	101	96	92	88	94	90	87	92	89	86	90	87	85	84	84	84	84
5	99	92	88	84	97	92	87	84	90	86	83	88	85	83	87	84	82	81	81	81	81
6	95	89	84	81	94	88	83	80	86	83	80	85	82	79	84	81	79	78	78	78	78
7	92	85	80	77	91	84	80	77	83	79	76	82	79	76	81	78	76	75	75	75	75
8	89	82	77	74	88	81	77	74	80	76	73	79	76	73	78	75	73	72	72	72	72
9	86	79	74	71	85	78	74	71	77	73	71	77	73	70	76	73	70	69	69	69	69
10	83	76	71	68	83	75	71	68	75	71	68	74	70	68	73	70	68	67	67	67	67

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	71431
5°	69546
10°	60336
15°	46550
20°	32436
25°	17094
30°	4773
35°	2115
40°	1059
45°	543
50°	239
55°	38
60°	0
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P710915

CATALOG NUMBER: LD6C05D010 EU6059027 6LBHYH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	114.7	23.0
10°-20°	224.2	45.1
20°-30°	129.6	26.0
30°-40°	22.7	4.6
40°-50°	5.8	1.2
50°-60°	0.7	0.1
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	468.5	94.1
0°-40°	491.3	98.7
0°-60°	497.7	100.0
0°-90°	497.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	497.7	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1303	
5°	1264	115
15°	820	224
25°	283	130
35°	32	23
45°	7	6
55°	0	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P710915

CATALOG NUMBER: LD6C05D010 EU6059027 6LBHYH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1303.0
2.5°	1300.8
5°	1263.8
7.5°	1186.1
10°	1083.9
12.5°	964.2
15°	820.2
17.5°	672.1
20°	556.0
22.5°	417.6
25°	282.6
27.5°	161.8
30°	75.4
32.5°	51.7
35°	31.6
37.5°	21.2
40°	14.8
42.5°	10.2
45°	7.0
47.5°	4.6
50°	2.8
52.5°	1.3
55°	0.4
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)