

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P685102

Luminaire Tested: **LX6C55D010 EX6559040 6LBMLI**

Issue Date: 2/15/2022

Test Information

Test Method: LM-79-08
Report Number: P685102
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205108)
Test Lab: INNOVATION CENTER
Issue Date: 2/15/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX6C55D010 EX6559040 6LBMLI
Description: 6 INCH 5500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, 90CRI LEDS
AND 6LBM TRIM WITH LI FINISH
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5478.0 lumens
Efficiency: N/A
Efficacy: 85.7 lumens/watt
Spacing Criteria (0/90/45): 0.85 / 0.85 / 0.85
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 63.9
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P685102
CATALOG NUMBER: LX6C55D010 EX6559040 6LBMLI

Luminous Intensity Polar Plot





TEST NUMBER: P685102

CATALOG NUMBER: LX6C55D010 EX6559040 6LBMLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	106	111	109	107	105	105	103	101	101	100	98	98	97	96	94			
2	108	103	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88			
3	103	97	92	88	101	95	91	87	93	89	86	90	87	85	88	85	83	82			
4	98	91	85	81	96	89	84	81	87	83	80	85	82	79	83	80	78	76			
5	93	85	79	75	91	84	79	75	82	78	74	81	77	73	79	76	73	71			
6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67			
7	84	75	69	65	83	75	69	65	73	68	65	72	68	64	71	67	64	63			
8	80	71	65	61	79	70	65	61	69	64	61	68	64	60	67	63	60	59			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55			
10	73	64	58	54	72	63	58	54	62	57	54	62	57	54	61	57	54	52			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	375820
5°	372242
10°	352732
15°	320252
20°	282988
25°	244653
30°	191238
35°	117283
40°	60198
45°	23917
50°	7769
55°	2676
60°	2291
65°	1829
70°	1138
75°	1504
80°	0
85°	0



TEST NUMBER: P685102

CATALOG NUMBER: LX6C55D010 EX6559040 6LBMLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	631.5	11.5
10°-20°	1572.3	28.7
20°-30°	1827.7	33.4
30°-40°	1119.3	20.4
40°-50°	277.9	5.1
50°-60°	32.5	0.6
60°-70°	12.1	0.2
70°-80°	4.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4031.6	73.6
0°-40°	5150.8	94.0
0°-60°	5461.2	99.7
0°-90°	5478.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5478.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6856	
5°	6764	632
15°	5643	1572
25°	4045	1828
35°	1752	1119
45°	308	278
55°	28	32
65°	14	12
75°	7	5
85°	0	0
90°	0	



TEST NUMBER: P685102

CATALOG NUMBER: LX6C55D010 EX6559040 6LBMLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	6855.5
2.5°	6848.4
5°	6764.4
7.5°	6582.0
10°	6336.6
12.5°	6014.3
15°	5642.8
17.5°	5243.2
20°	4850.8
22.5°	4458.1
25°	4044.7
27.5°	3568.0
30°	3021.1
32.5°	2383.3
35°	1752.5
37.5°	1233.6
40°	841.2
42.5°	525.6
45°	308.5
47.5°	175.3
50°	91.1
52.5°	42.1
55°	28.0
57.5°	20.9
60°	20.9
62.5°	14.1
65°	14.1
67.5°	7.1
70°	7.1
72.5°	7.1
75°	7.1
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)