

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P685127

Luminaire Tested: **LX6C60D010 EX6609040 6LBMLI**

Issue Date: 2/15/2022

Test Information

Test Method: LM-79-08
Report Number: P685127
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205108)
Test Lab: INNOVATION CENTER
Issue Date: 2/15/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX6C60D010 EX6609040 6LBMLI
Description: 6 INCH 6000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, 90CRI LEDS
AND 6LBM TRIM WITH LI FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5922.9 lumens
Efficiency: N/A
Efficacy: 82.3 lumens/watt
Spacing Criteria (0/90/45): 0.85 / 0.85 / 0.85
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 72
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P685127

CATALOG NUMBER: LX6C60D010 EX6609040 6LBMLI

Luminous Intensity Polar Plot





TEST NUMBER: P685127

CATALOG NUMBER: LX6C60D010 EX6609040 6LBMLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	106	111	109	107	105	105	103	101	101	100	98	98	97	96	94			
2	108	103	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88			
3	103	97	92	88	101	95	91	87	93	89	86	90	87	85	88	85	83	82			
4	98	91	85	81	96	89	84	81	87	83	80	85	82	79	83	80	78	76			
5	93	85	79	75	91	84	79	75	82	78	74	81	77	73	79	76	73	71			
6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67			
7	84	75	69	65	83	75	69	65	73	68	65	72	68	64	71	67	64	63			
8	80	71	65	61	79	70	65	61	69	64	61	68	64	60	67	63	60	59			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55			
10	73	64	58	54	72	63	58	54	62	57	54	62	57	54	61	57	54	52			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	406344
5°	402481
10°	381389
15°	346262
20°	305973
25°	264523
30°	206779
35°	126806
40°	65086
45°	25855
50°	8392
55°	2896
60°	2478
65°	1985
70°	1218
75°	1610
80°	0
85°	0



TEST NUMBER: P685127

CATALOG NUMBER: LX6C60D010 EX6609040 6LBMLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	682.8	11.5
10°-20°	1700.0	28.7
20°-30°	1976.2	33.4
30°-40°	1210.2	20.4
40°-50°	300.5	5.1
50°-60°	35.1	0.6
60°-70°	13.1	0.2
70°-80°	5.0	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4359.1	73.6
0°-40°	5569.2	94.0
0°-60°	5904.8	99.7
0°-90°	5922.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5922.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	7412	
5°	7314	683
15°	6101	1700
25°	4373	1976
35°	1895	1210
45°	334	300
55°	30	35
65°	15	13
75°	8	5
85°	0	0
90°	0	



TEST NUMBER: P685127

CATALOG NUMBER: LX6C60D010 EX6609040 6LBMLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	7412.3
2.5°	7404.7
5°	7313.9
7.5°	7116.7
10°	6851.4
12.5°	6502.8
15°	6101.1
17.5°	5669.2
20°	5244.8
22.5°	4820.2
25°	4373.2
27.5°	3857.8
30°	3266.6
32.5°	2576.9
35°	1894.8
37.5°	1333.8
40°	909.5
42.5°	568.3
45°	333.5
47.5°	189.5
50°	98.4
52.5°	45.5
55°	30.3
57.5°	22.6
60°	22.6
62.5°	15.3
65°	15.3
67.5°	7.6
70°	7.6
72.5°	7.6
75°	7.6
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)