

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P684678

Luminaire Tested: **LX6C90D010 EX6C909027 6LBMDH**

Issue Date: 2/15/2022



**Test Information**

Test Method: LM-79-08  
Report Number: P684678  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-21)  
Test Lab: INNOVATION CENTER  
Issue Date: 2/15/2022  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LX6C90D010 EX6C909027 6LBMDH  
Description: 6 INCH 9000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 2700K, 90CRI LEDS  
AND 6LRMD45 TRIM WITH H FINISH  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 6738.0 lumens  
Efficiency: N/A  
Efficacy: 69.4 lumens/watt  
Spacing Criteria (0/90/45): 0.8 / 0.8 / 0.8  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 97.1  
Input Voltage (V):  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P684678

CATALOG NUMBER: LX6C90D010 EX6C909027 6LBMDH

### Luminous Intensity Polar Plot





TEST NUMBER: P684678

CATALOG NUMBER: LX6C90D010 EX6C909027 6LBMDH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	93			
2	108	103	99	96	106	101	98	94	98	95	92	95	93	90	92	90	89	87			
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81			
4	97	90	84	80	95	89	83	80	86	82	79	84	81	78	83	79	77	75			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70			
6	88	79	73	69	86	78	73	69	77	72	68	75	71	68	74	70	67	66			
7	84	74	68	64	82	74	68	64	72	67	64	71	67	63	70	66	63	62			
8	80	70	64	60	78	70	64	60	68	63	60	67	63	59	66	62	59	58			
9	76	66	60	56	75	66	60	56	65	60	56	64	59	56	63	59	56	54			
10	72	63	57	53	71	62	57	53	62	56	53	61	56	53	60	56	53	51			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	485493
5°	470470
10°	433220
15°	388572
20°	345737
25°	287109
30°	205120
35°	131852
40°	80343
45°	44664
50°	19786
55°	11460
60°	7543
65°	5357
70°	3783
75°	2923
80°	1863
85°	1258



TEST NUMBER: P684678

CATALOG NUMBER: LX6C90D010 EX6C909027 6LBMDH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	791.4	11.7
10°-20°	1915.5	28.4
20°-30°	2130.2	31.6
30°-40°	1262.2	18.7
40°-50°	462.4	6.9
50°-60°	116.2	1.7
60°-70°	42.4	0.6
70°-80°	14.8	0.2
80°-90°	3.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4837.1	71.8
0°-40°	6099.3	90.5
0°-60°	6677.8	99.1
0°-90°	6738.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6738.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	8856	
5°	8549	791
15°	6847	1915
25°	4747	2130
35°	1970	1262
45°	576	462
55°	120	116
65°	41	42
75°	14	15
85°	2	3
90°	0	



TEST NUMBER: P684678

CATALOG NUMBER: LX6C90D010 EX6C909027 6LBMDH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	8856.1
2.5°	8777.5
5°	8549.4
7.5°	8203.3
10°	7782.5
12.5°	7318.5
15°	6846.6
17.5°	6388.4
20°	5926.4
22.5°	5389.6
25°	4746.6
27.5°	4007.3
30°	3240.4
32.5°	2554.2
35°	1970.2
37.5°	1496.3
40°	1122.7
42.5°	818.0
45°	576.1
47.5°	365.7
50°	232.0
52.5°	163.2
55°	119.9
57.5°	90.4
60°	68.8
62.5°	53.1
65°	41.3
67.5°	31.5
70°	23.6
72.5°	17.7
75°	13.8
77.5°	9.8
80°	5.9
82.5°	3.9
85°	2.0
87.5°	2.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)