

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P685273

Luminaire Tested: **LX6C90D010 EX6909035 6LBNLI**

Issue Date: 2/14/2022

**Test Information**

Test Method: LM-79-08  
Report Number: P685273  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205310)  
Test Lab: INNOVATION CENTER  
Issue Date: 2/14/2022  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LX6C90D010 EX6909035 6LBNLI  
Description: 6 INCH 9000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3500K, 90CRI LEDS  
AND 6LBN TRIM WITH LI FINISH  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 7810.0 lumens  
Efficiency: N/A  
Efficacy: 80.4 lumens/watt  
Spacing Criteria (0/90/45): 0.53 / 0.53 / 0.58  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 97.1  
Input Voltage (V):  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P685273

CATALOG NUMBER: LX6C90D010 EX6909035 6LBNLI

### Luminous Intensity Polar Plot





TEST NUMBER: P685273

CATALOG NUMBER: LX6C90D010 EX6909035 6LBNLI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	112	109	107	112	109	107	106	105	104	102	102	101	99	98	97	96	95			
2	109	105	101	98	107	103	100	97	100	97	95	97	95	93	94	93	91	89			
3	105	99	94	91	103	97	93	90	95	91	89	93	90	87	90	88	86	85			
4	100	93	88	85	98	92	88	84	90	86	83	88	85	82	86	84	81	80			
5	96	88	83	79	94	87	83	79	86	82	78	84	81	78	83	80	77	76			
6	92	84	79	75	90	83	78	75	82	77	74	80	76	74	79	76	73	72			
7	88	80	74	71	87	79	74	71	78	73	70	77	73	70	76	72	69	68			
8	84	76	71	67	83	75	70	67	74	70	67	73	69	66	73	69	66	65			
9	81	73	67	64	80	72	67	64	71	67	63	70	66	63	70	66	63	62			
10	78	69	64	61	77	69	64	61	68	64	61	67	63	60	67	63	60	59			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	974785
5°	911592
10°	743473
15°	547097
20°	377094
25°	279954
30°	210286
35°	131129
40°	63655
45°	21839
50°	2866
55°	2170
60°	1239
65°	1466
70°	1811
75°	0
80°	0
85°	0



TEST NUMBER: P685273

CATALOG NUMBER: LX6C90D010 EX6909035 6LBNLI

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	1478.4	18.9
10°-20°	2653.6	34.0
20°-30°	2145.5	27.5
30°-40°	1235.9	15.8
40°-50°	261.3	3.3
50°-60°	22.6	0.3
60°-70°	11.2	0.1
70°-80°	1.5	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6277.5	80.4
0°-40°	7513.5	96.2
0°-60°	7797.3	99.8
0°-90°	7810.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7810.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	17782	
5°	16566	###
15°	9640	2654
25°	4628	2146
35°	1959	1236
45°	282	261
55°	23	23
65°	11	11
75°	0	1
85°	0	0
90°	0	



TEST NUMBER: P685273

CATALOG NUMBER: LX6C90D010 EX6909035 6LBNLI

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	17781.5
2.5°	17567.9
5°	16565.5
7.5°	15124.0
10°	13356.0
12.5°	11543.0
15°	9639.8
17.5°	7804.2
20°	6463.9
22.5°	5439.3
25°	4628.3
27.5°	3941.6
30°	3322.0
32.5°	2635.3
35°	1959.4
37.5°	1362.5
40°	889.5
42.5°	540.6
45°	281.7
47.5°	112.5
50°	33.6
52.5°	33.6
55°	22.7
57.5°	22.7
60°	11.3
62.5°	11.3
65°	11.3
67.5°	11.3
70°	11.3
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)