

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P684712

Luminaire Tested: **LX6C90D010 EX6C909727 6LBSH**

Issue Date: 2/15/2022

**Test Information**

Test Method: LM-79-08  
Report Number: P684712  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P204188)  
Test Lab: INNOVATION CENTER  
Issue Date: 2/15/2022  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LX6C90D010 EX6C909727 6LBSH  
Description: 6 INCH 9000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 2700K, 97CRI LEDS  
AND 6LBS TRIM WITH H FINISH  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 9704.0 lumens  
Efficiency: N/A  
Efficacy: 99.9 lumens/watt  
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 97.1  
Input Voltage (V):  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P684712

CATALOG NUMBER: LX6C90D010 EX6C909727 6LBSH

### Luminous Intensity Polar Plot





TEST NUMBER: P684712

CATALOG NUMBER: LX6C90D010 EX6C909727 6LBSH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77			
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67			
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51			
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46			
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41			
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37			
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34			
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	278223
5°	276925
10°	271210
15°	261347
20°	249327
25°	235889
30°	222509
35°	209509
40°	197277
45°	183887
50°	167670
55°	148086
60°	125341
65°	98415
70°	70220
75°	38464
80°	6787
85°	0



TEST NUMBER: P684712

CATALOG NUMBER: LX6C90D010 EX6C909727 6LBSH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	475.4	4.9
10°-20°	1292.1	13.3
20°-30°	1794.4	18.5
30°-40°	1958.1	20.2
40°-50°	1826.6	18.8
50°-60°	1386.5	14.3
60°-70°	759.2	7.8
70°-80°	208.9	2.2
80°-90°	2.9	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3561.8	36.7
0°-40°	5519.9	56.9
0°-60°	8733.0	90.0
0°-90°	9704.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	9704.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	5075	
5°	5032	475
15°	4605	1292
25°	3900	1794
35°	3131	1958
45°	2372	1827
55°	1549	1386
65°	759	759
75°	182	209
85°	0	3
90°	0	



TEST NUMBER: P684712

CATALOG NUMBER: LX6C90D010 EX6C909727 6LBSH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	5075.2
2.5°	5075.2
5°	5032.3
7.5°	4968.2
10°	4872.1
12.5°	4743.9
15°	4604.9
17.5°	4434.0
20°	4273.8
22.5°	4081.5
25°	3899.8
27.5°	3718.2
30°	3515.1
32.5°	3322.8
35°	3130.6
37.5°	2938.3
40°	2756.7
42.5°	2564.3
45°	2371.9
47.5°	2179.6
50°	1966.0
52.5°	1762.9
55°	1549.4
57.5°	1346.3
60°	1143.2
62.5°	940.3
65°	758.7
67.5°	587.6
70°	438.1
72.5°	299.1
75°	181.6
77.5°	85.6
80°	21.5
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)