

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P785756

Luminaire Tested: LERS6D05D010-EC6DR300210IC9040-6LBS1B

Issue Date: 2/2/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P785756  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-16)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/2/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LERS6D05D010-EC6DR300210IC9040-6LBS1B  
Description: 6 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 30° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1205.9 lumens  
Efficiency: N/A  
Efficacy: 160.8 lumens/watt  
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.49  
Luminous Opening: Rectangular (W 0.38' x L: 0.38' x H: 0')  
CIE Type: Direct

Input Watts (W): 7.5  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT




Downlight

TEST NUMBER: P785756

CATALOG NUMBER: LERS6D05D010-EC6DR300210IC9040-6LBS1B

### Luminous Intensity Polar Plot





TEST NUMBER: P785756

CATALOG NUMBER: LERS6D05D010-EC6DR300210IC9040-6LBS1B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0													
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						100													
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96						96													
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92						92													
3	107	102	98	95	105	101	97	94	98	95	93	96	93	91	94	92	90	89						89													
4	103	98	93	90	102	96	93	90	94	91	89	93	90	88	91	89	87	85						85													
5	100	94	89	86	98	93	89	86	91	88	85	90	86	84	88	86	83	82						82													
6	97	90	85	82	95	89	85	82	88	84	81	87	83	81	85	83	80	79						79													
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77						77													
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74						74													
9	88	81	76	73	87	80	76	73	80	76	73	79	75	73	78	75	73	72						72													
10	85	78	74	71	85	78	74	71	77	73	71	76	73	71	76	73	70	69						69													

**AVERAGE LUMINANCE (cd/sqm):**

	0°	45°	90°
0°	296805	296805	296805
5°	288280	287942	288296
10°	249697	247932	249635
15°	162917	162037	161221
20°	81008	84046	80902
25°	40809	46020	39973
30°	16342	17801	14239
35°	7578	7260	6083
40°	3267	3637	3078
45°	2306	2869	2327
50°	798	2084	834
55°	454	867	480
60°	321	383	321
65°	199	199	199
70°	134	90	134
75°	0	59	0
80°	0	0	0
85°	0	0	0

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 22.5°  
 Vertical Angle: 45°  
 Luminance: 2869 cd/sqm



TEST NUMBER: P785756

CATALOG NUMBER: LERS6D05D010-EC6DR300210IC9040-6LBS1B

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	341.0	28.3
10°-20°	549.1	45.5
20°-30°	237.3	19.7
30°-40°	54.1	4.5
40°-50°	18.6	1.5
50°-60°	4.5	0.4
60°-70°	1.2	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1127.4	93.5
0°-40°	1181.5	98.0
0°-60°	1204.6	99.9
0°-90°	1205.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1205.9	100.0

**CANDELA DISTRIBUTION:**

	0°	22.5°	45°	67.5°	90°	Flux
0°	3878	3878	3878	3878	3878	
5°	3752	3748	3748	3755	3752	341
15°	2056	2031	2045	2038	2034	550
25°	483	501	545	489	473	231
35°	81	83	78	77	65	55
45°	21	26	26	26	22	15
55°	3	4	6	4	4	3
65°	1	1	1	1	1	1
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	



TEST NUMBER: P785756

CATALOG NUMBER: LERS6D05D010-EC6DR300210IC9040-6LBS1B

**CANDELA DISTRIBUTION (FULL):**

	0°	22.5°	45°	67.5°	90°
0°	3877.6	3877.6	3877.6	3877.6	3877.6
2.5°	3851.9	3849.2	3850.7	3852.6	3853.4
5°	3751.9	3748.3	3747.5	3755.3	3752.1
7.5°	3550.3	3545.2	3537.4	3555.1	3571.6
10°	3212.6	3206.9	3189.9	3198.3	3211.8
12.5°	2714.0	2695.5	2695.1	2721.8	2718.2
15°	2055.9	2031.1	2044.8	2038.2	2034.5
17.5°	1382.5	1373.0	1391.3	1385.7	1361.9
20°	994.5	997.0	1031.8	1014.3	993.2
22.5°	725.7	734.7	776.0	730.8	714.3
25°	483.2	501.4	544.9	488.7	473.3
27.5°	297.2	305.6	349.5	293.4	285.0
30°	184.9	180.7	201.4	172.9	161.1
32.5°	121.3	115.9	122.6	110.0	100.5
35°	81.1	82.8	77.7	77.1	65.1
37.5°	50.6	58.3	51.4	54.8	41.9
40°	32.7	42.3	36.4	40.2	30.8
42.5°	26.8	32.6	29.9	31.8	27.4
45°	21.3	26.5	26.5	26.5	21.5
47.5°	11.8	17.7	22.7	18.1	12.6
50°	6.7	8.9	17.5	9.3	7.0
52.5°	4.6	5.1	12.0	5.3	4.8
55°	3.4	3.6	6.5	3.8	3.6
57.5°	2.7	2.9	3.4	2.9	2.7
60°	2.1	2.1	2.5	2.3	2.1
62.5°	1.5	1.5	1.7	1.5	1.5
65°	1.1	1.1	1.1	1.1	1.1
67.5°	0.6	0.8	0.8	0.8	0.8
70°	0.6	0.4	0.4	0.4	0.6
72.5°	0.4	0.2	0.2	0.2	0.2
75°	0.0	0.0	0.2	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report







— 0°-180°    - - 45°-225°    - - - - 90°-270°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)