

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P785835

Luminaire Tested: LERS6D05D010-EC6DR450210IC9050-6LBS1MW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P785835
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LERS6D05D010-EC6DR450210IC9050-6LBS1MW
Description: 6 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 45° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1265.8 lumens
Efficiency: N/A
Efficacy: 168.8 lumens/watt
Spacing Criteria (0/90/45): 0.75 / 0.75 / 0.69
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 7.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P785835

CATALOG NUMBER: LERS6D05D010-EC6DR450210IC9050-6LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P785835

CATALOG NUMBER: LERS6D05D010-EC6DR450210IC9050-6LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20		
RC	80				70				50				30				10		
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30
RCR																			
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	98	98	97	95	95
2	109	105	102	99	107	103	100	98	100	98	95	97	95	93	95	93	91	90	90
3	105	99	95	91	103	98	94	91	95	92	89	93	90	88	91	89	87	85	85
4	100	94	89	85	99	93	88	85	91	87	84	89	86	83	87	84	82	81	81
5	96	89	84	80	95	88	83	80	86	82	79	85	81	79	83	80	78	77	77
6	92	85	80	76	91	84	79	76	83	78	75	81	77	75	80	77	74	73	73
7	89	81	75	72	87	80	75	72	79	74	71	78	74	71	77	73	71	69	69
8	85	77	72	68	84	76	71	68	75	71	68	74	70	67	73	70	67	66	66
9	82	73	68	65	81	73	68	65	72	68	65	71	67	64	71	67	64	63	63
10	79	70	65	62	78	70	65	62	69	65	62	68	64	61	68	64	61	60	60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	244449
5°	237486
10°	227218
15°	207951
20°	164980
25°	102991
30°	56774
35°	25489
40°	10041
45°	4728
50°	2244
55°	1181
60°	568
65°	129
70°	64
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 4728 cd/sqm



TEST NUMBER: P785835

CATALOG NUMBER: LERS6D05D010-EC6DR450210IC9050-6LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	203.5	16.1
10°-20°	500.7	39.6
20°-30°	396.5	31.3
30°-40°	132.0	10.4
40°-50°	26.2	2.1
50°-60°	5.9	0.5
60°-70°	0.9	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1100.7	87.0
0°-40°	1232.8	97.4
0°-60°	1264.9	99.9
0°-90°	1265.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1265.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2237	
5°	2165	203
15°	1838	501
25°	854	397
35°	191	132
45°	31	26
55°	6	6
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P785835

CATALOG NUMBER: LERS6D05D010-EC6DR450210IC9050-6LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	2237.3
2.5°	2222.7
5°	2165.3
7.5°	2118.0
10°	2048.0
12.5°	1954.7
15°	1838.4
17.5°	1663.5
20°	1418.9
22.5°	1127.5
25°	854.3
27.5°	625.6
30°	450.0
32.5°	306.0
35°	191.1
37.5°	113.3
40°	70.4
42.5°	46.3
45°	30.6
47.5°	19.7
50°	13.2
52.5°	8.8
55°	6.2
57.5°	4.0
60°	2.6
62.5°	1.4
65°	0.5
67.5°	0.2
70°	0.2
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)