

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P786367

Luminaire Tested: LERS6D10D010-EC6DR300210IC9024-6LBS1MW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P786367
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-16)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LERS6D10D010-EC6DR300210IC9024-6LBS1MW
Description: 6 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 30° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1546.4 lumens
Efficiency: N/A
Efficacy: 132.2 lumens/watt
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.49
Luminous Opening: Rectangular (W 0.38' x L: 0.38' x H: 0')
CIE Type: Direct

Input Watts (W): 11.7
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P786367

CATALOG NUMBER: LERS6D10D010-EC6DR300210IC9024-6LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P786367

CATALOG NUMBER: LERS6D10D010-EC6DR300210IC9024-6LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0													
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						100													
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96						96													
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92						92													
3	107	102	98	95	105	101	97	94	98	95	93	96	93	91	94	92	90	89						89													
4	103	98	93	90	102	96	93	90	94	91	89	93	90	88	91	89	87	85						85													
5	100	94	89	86	98	93	89	86	91	88	85	90	86	84	88	86	83	82						82													
6	97	90	85	82	95	89	85	82	88	84	81	87	83	81	85	83	80	79						79													
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77						77													
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74						74													
9	88	81	76	73	87	80	76	73	80	76	73	79	75	73	78	75	73	72						72													
10	85	78	74	71	85	78	74	71	77	73	71	76	73	71	76	73	70	69						69													

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	380597	380597	380597
5°	369672	369234	369688
10°	320193	317931	320115
15°	208910	207785	206739
20°	103881	107774	103742
25°	52329	59010	51257
30°	20947	22830	18251
35°	9718	9307	7802
40°	4197	4656	3947
45°	2955	3670	2988
50°	1012	2679	1072
55°	587	1108	614
60°	413	490	413
65°	272	272	272
70°	157	112	157
75°	0	59	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 22.5°
 Vertical Angle: 45°
 Luminance: 3670 cd/sqm



TEST NUMBER: P786367

CATALOG NUMBER: LERS6D10D010-EC6DR300210IC9024-6LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	437.2	28.3
10°-20°	704.2	45.5
20°-30°	304.3	19.7
30°-40°	69.4	4.5
40°-50°	23.8	1.5
50°-60°	5.8	0.4
60°-70°	1.5	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1445.7	93.5
0°-40°	1515.1	98.0
0°-60°	1544.7	99.9
0°-90°	1546.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1546.4	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	4972	4972	4972	4972	4972	
5°	4811	4806	4806	4816	4811	438
15°	2636	2604	2622	2614	2609	706
25°	620	643	699	627	607	297
35°	104	106	100	99	84	71
45°	27	34	34	34	28	19
55°	4	5	8	5	5	4
65°	2	2	2	2	2	1
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	



TEST NUMBER: P786367

CATALOG NUMBER: LERS6D10D010-EC6DR300210IC9024-6LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	4972.3	4972.3	4972.3	4972.3	4972.3
2.5°	4939.3	4935.9	4937.9	4940.3	4941.3
5°	4811.2	4806.5	4805.5	4815.5	4811.4
7.5°	4552.6	4546.0	4536.0	4558.7	4580.0
10°	4119.6	4112.2	4090.5	4101.2	4118.6
12.5°	3480.2	3456.5	3456.0	3490.2	3485.6
15°	2636.3	2604.5	2622.1	2613.6	2608.9
17.5°	1772.8	1760.6	1784.0	1777.0	1746.4
20°	1275.3	1278.5	1323.1	1300.7	1273.6
22.5°	930.6	942.1	995.0	937.2	915.9
25°	619.6	643.0	698.7	626.7	606.9
27.5°	381.1	391.8	448.2	376.2	365.5
30°	237.0	231.7	258.3	221.7	206.5
32.5°	155.5	148.7	157.2	141.1	128.9
35°	104.0	106.2	99.6	98.9	83.5
37.5°	64.9	74.7	65.9	70.3	53.7
40°	42.0	54.2	46.6	51.5	39.5
42.5°	34.4	41.7	38.3	40.8	35.2
45°	27.3	33.9	33.9	33.9	27.6
47.5°	15.1	22.7	29.1	23.2	16.1
50°	8.5	11.5	22.5	12.0	9.0
52.5°	5.9	6.6	15.4	6.8	6.1
55°	4.4	4.6	8.3	4.9	4.6
57.5°	3.4	3.7	4.4	3.7	3.4
60°	2.7	2.7	3.2	2.9	2.7
62.5°	2.0	2.0	2.2	2.0	2.0
65°	1.5	1.5	1.5	1.5	1.5
67.5°	0.7	1.0	1.0	1.0	1.0
70°	0.7	0.5	0.5	0.5	0.7
72.5°	0.5	0.2	0.2	0.2	0.2
75°	0.0	0.0	0.2	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report





— 0°-180° - - 45°-225° - - - - 90°-270°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)