

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P786672

Luminaire Tested: LERS6D15D010-EC6DR300215IC9024-6LBS1B

Issue Date: 2/2/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P786672  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-16)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/2/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LERS6D15D010-EC6DR300215IC9024-6LBS1B  
Description: 6 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 30° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 2049.5 lumens  
Efficiency: N/A  
Efficacy: 129.7 lumens/watt  
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.49  
Luminous Opening: Rectangular (W 0.38' x L: 0.38' x H: 0')  
CIE Type: Direct

Input Watts (W): 15.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT




Downlight

TEST NUMBER: P786672

CATALOG NUMBER: LERS6D15D010-EC6DR300215IC9024-6LBS1B

### Luminous Intensity Polar Plot





TEST NUMBER: P786672

CATALOG NUMBER: LERS6D15D010-EC6DR300215IC9024-6LBS1B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0													
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						100													
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96						96													
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92						92													
3	107	102	98	95	105	101	97	94	98	95	93	96	93	91	94	92	90	89						89													
4	103	98	93	90	102	96	93	90	94	91	89	93	90	88	91	89	87	85						85													
5	100	94	89	86	98	93	89	86	91	88	85	90	86	84	88	86	83	82						82													
6	97	90	85	82	95	89	85	82	88	84	81	87	83	81	85	83	80	79						79													
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77						77													
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74						74													
9	88	81	76	73	87	80	76	73	80	76	73	79	75	73	78	75	73	72						72													
10	85	78	74	71	85	78	74	71	77	73	71	76	73	71	76	73	70	69						69													

**AVERAGE LUMINANCE (cd/sqm):**

	0°	45°	90°
0°	504436	504436	504436
5°	489951	489382	489974
10°	424374	421382	424273
15°	276885	275395	274008
20°	137685	142849	137497
25°	69356	78207	67937
30°	27770	30254	24191
35°	12876	12334	10344
40°	5566	6175	5236
45°	3919	4871	3962
50°	1346	3549	1429
55°	774	1468	814
60°	551	643	551
65°	344	344	344
70°	224	134	224
75°	0	89	0
80°	0	0	0
85°	0	0	0

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 22.5°

Vertical Angle: 45°

Luminance: 4871 cd/sqm



TEST NUMBER: P786672

CATALOG NUMBER: LERS6D15D010-EC6DR300215IC9024-6LBS1B

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	579.5	28.3
10°-20°	933.3	45.5
20°-30°	403.3	19.7
30°-40°	91.9	4.5
40°-50°	31.6	1.5
50°-60°	7.7	0.4
60°-70°	2.0	0.1
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1916.1	93.5
0°-40°	2008.0	98.0
0°-60°	2047.3	99.9
0°-90°	2049.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2049.5	100.0

**CANDELA DISTRIBUTION:**

	0°	22.5°	45°	67.5°	90°	Flux
0°	6590	6590	6590	6590	6590	
5°	6377	6370	6369	6382	6377	580
15°	3494	3452	3475	3464	3458	936
25°	821	852	926	831	804	393
35°	138	141	132	131	111	93
45°	36	45	45	45	37	26
55°	6	6	11	6	6	6
65°	2	2	2	2	2	2
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	0



TEST NUMBER: P786672

CATALOG NUMBER: LERS6D15D010-EC6DR300215IC9024-6LBS1B

**CANDELA DISTRIBUTION (FULL):**

	0°	22.5°	45°	67.5°	90°
0°	6590.2	6590.2	6590.2	6590.2	6590.2
2.5°	6546.5	6542.0	6544.5	6547.8	6549.1
5°	6376.6	6370.5	6369.2	6382.4	6376.9
7.5°	6034.0	6025.2	6012.0	6042.1	6070.2
10°	5460.0	5450.3	5421.5	5435.7	5458.7
12.5°	4612.6	4581.2	4580.6	4625.9	4619.7
15°	3494.1	3452.0	3475.3	3464.0	3457.8
17.5°	2349.7	2333.5	2364.5	2355.2	2314.7
20°	1690.3	1694.5	1753.7	1723.9	1688.0
22.5°	1233.4	1248.6	1318.8	1242.1	1214.0
25°	821.2	852.2	926.0	830.6	804.4
27.5°	505.1	519.3	594.0	498.6	484.4
30°	314.2	307.1	342.3	293.8	273.7
32.5°	206.1	197.0	208.4	187.0	170.8
35°	137.8	140.7	132.0	131.0	110.7
37.5°	86.1	99.0	87.4	93.2	71.2
40°	55.7	71.8	61.8	68.3	52.4
42.5°	45.6	55.3	50.8	54.0	46.6
45°	36.2	45.0	45.0	45.0	36.6
47.5°	20.1	30.1	38.5	30.7	21.4
50°	11.3	15.2	29.8	15.9	12.0
52.5°	7.8	8.7	20.4	9.1	8.1
55°	5.8	6.1	11.0	6.5	6.1
57.5°	4.5	4.9	5.8	4.9	4.5
60°	3.6	3.6	4.2	3.9	3.6
62.5°	2.6	2.6	2.9	2.6	2.6
65°	1.9	1.9	1.9	1.9	1.9
67.5°	1.0	1.3	1.3	1.3	1.3
70°	1.0	0.6	0.6	0.6	1.0
72.5°	0.6	0.3	0.3	0.3	0.3
75°	0.0	0.0	0.3	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report







— 0°-180°    - - 45°-225°    - - - - 90°-270°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)