

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P789231

Luminaire Tested: LER6D10D010-EC6DR600210IC9024-6LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P789231
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D10D010-EC6DR600210IC9024-6LBDP1B
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1249.7 lumens
Efficiency: N/A
Efficacy: 106.8 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 11.7
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P789231

CATALOG NUMBER: LER6D10D010-EC6DR600210IC9024-6LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P789231

CATALOG NUMBER: LER6D10D010-EC6DR600210IC9024-6LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100																
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93			93																
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86			86																
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80			80																
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75			75																
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70			70																
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66			66																
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62			62																
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59			59																
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55			55																
10	73	64	58	54	72	63	58	54	63	58	54	62	57	54	61	57	54	53			53																

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	162176
5°	166162
10°	168172
15°	160205
20°	141248
25°	114251
30°	77275
35°	38721
40°	6276
45°	6150
50°	6272
55°	6362
60°	6534
65°	6696
70°	6836
75°	6923
80°	6670
85°	5516

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 75°
 Luminance: 6923 cd/sqm



TEST NUMBER: P789231

CATALOG NUMBER: LER6D10D010-EC6DR600210IC9024-6LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	144.8	11.6
10°-20°	391.8	31.3
20°-30°	421.5	33.7
30°-40°	183.2	14.7
40°-50°	30.8	2.5
50°-60°	29.9	2.4
60°-70°	25.6	2.0
70°-80°	17.1	1.4
80°-90°	5.1	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	958.1	76.7
0°-40°	1141.3	91.3
0°-60°	1202.0	96.2
0°-90°	1249.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1249.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1484	
5°	1515	145
15°	1416	392
25°	948	422
35°	290	183
45°	40	31
55°	33	30
65°	26	26
75°	16	17
85°	4	5
90°	0	



TEST NUMBER: P789231

CATALOG NUMBER: LER6D10D010-EC6DR600210IC9024-6LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	1484.3
2.5°	1526.0
5°	1515.0
7.5°	1518.5
10°	1515.8
12.5°	1484.5
15°	1416.3
17.5°	1324.7
20°	1214.8
22.5°	1097.2
25°	947.7
27.5°	758.0
30°	612.5
32.5°	472.1
35°	290.3
37.5°	124.2
40°	44.0
42.5°	40.6
45°	39.8
47.5°	38.4
50°	36.9
52.5°	35.2
55°	33.4
57.5°	31.7
60°	29.9
62.5°	28.0
65°	25.9
67.5°	23.8
70°	21.4
72.5°	18.9
75°	16.4
77.5°	13.5
80°	10.6
82.5°	7.5
85°	4.4
87.5°	1.5
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)