

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P789367

Luminaire Tested: LER6D10D010-EC6DR700210IC9050-6LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P789367
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D10D010-EC6DR700210IC9050-6LBDP1B
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1142.2 lumens
Efficiency: N/A
Efficacy: 97.6 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 11.7
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P789367

CATALOG NUMBER: LER6D10D010-EC6DR700210IC9050-6LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P789367

CATALOG NUMBER: LER6D10D010-EC6DR700210IC9050-6LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	140302
5°	136132
10°	132337
15°	130603
20°	121959
25°	91622
30°	64772
35°	22942
40°	12066
45°	12856
50°	13309
55°	13563
60°	13636
65°	13340
70°	12587
75°	11694
80°	10382
85°	8399

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 13645 cd/sqm



TEST NUMBER: P789367

CATALOG NUMBER: LER6D10D010-EC6DR700210IC9050-6LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	117.1	10.3
10°-20°	321.1	28.1
20°-30°	353.7	31.0
30°-40°	135.1	11.8
40°-50°	63.8	5.6
50°-60°	63.4	5.6
60°-70°	50.8	4.4
70°-80°	29.2	2.6
80°-90°	7.9	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	791.9	69.3
0°-40°	927.0	81.2
0°-60°	1054.3	92.3
0°-90°	1142.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1142.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1284	
5°	1241	117
15°	1155	321
25°	760	354
35°	172	135
45°	83	64
55°	71	63
65°	52	51
75°	28	29
85°	7	8
90°	0	



TEST NUMBER: P789367

CATALOG NUMBER: LER6D10D010-EC6DR700210IC9050-6LBDP1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	1284.1
2.5°	1270.7
5°	1241.2
7.5°	1216.6
10°	1192.8
12.5°	1172.7
15°	1154.6
17.5°	1110.9
20°	1048.9
22.5°	915.1
25°	760.0
27.5°	661.6
30°	513.4
32.5°	331.6
35°	172.0
37.5°	92.9
40°	84.6
42.5°	84.0
45°	83.2
47.5°	81.3
50°	78.3
52.5°	74.8
55°	71.2
57.5°	67.1
60°	62.4
62.5°	57.1
65°	51.6
67.5°	45.5
70°	39.4
72.5°	33.3
75°	27.7
77.5°	21.8
80°	16.5
82.5°	11.6
85°	6.7
87.5°	2.6
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)