

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P790551

Luminaire Tested: LER6D20D010-EC6DR6520359050-6LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P790551
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D20D010-EC6DR6520359050-6LBDDP1B
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2342.2 lumens
Efficiency: N/A
Efficacy: 101.4 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 23.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P790551
CATALOG NUMBER: LER6D20D010-EC6DR6520359050-6LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P790551

CATALOG NUMBER: LER6D20D010-EC6DR6520359050-6LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93																			
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87																			
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80																			
4	97	89	84	79	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	83	78	73	90	83	77	73	81	76	72	79	75	72	77	74	71	69																			
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65																			
7	83	73	67	63	81	73	67	63	71	66	62	70	66	62	69	65	62	60																			
8	79	69	63	59	77	68	63	59	67	62	58	66	62	58	65	61	58	57																			
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	58	54	53																			
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	251955
5°	252161
10°	261034
15°	261477
20°	240731
25°	205114
30°	157023
35°	110934
40°	65481
45°	26577
50°	9638
55°	5372
60°	3081
65°	1706
70°	1789
75°	1393
80°	1447
85°	1254

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 26577 cd/sqm



TEST NUMBER: P790551

CATALOG NUMBER: LER6D20D010-EC6DR6520359050-6LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	222.0	9.5
10°-20°	640.5	27.3
20°-30°	768.5	32.8
30°-40°	516.5	22.1
40°-50°	154.6	6.6
50°-60°	27.3	1.2
60°-70°	7.8	0.3
70°-80°	3.8	0.2
80°-90°	1.2	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1631.0	69.6
0°-40°	2147.5	91.7
0°-60°	2329.4	99.5
0°-90°	2342.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2342.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2306	
5°	2299	222
15°	2312	641
25°	1701	768
35°	832	516
45°	172	155
55°	28	27
65°	7	8
75°	3	4
85°	1	1
90°	0	



TEST NUMBER: P790551

CATALOG NUMBER: LER6D20D010-EC6DR6520359050-6LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	2306.0
2.5°	2315.8
5°	2299.1
7.5°	2333.8
10°	2352.8
12.5°	2348.3
15°	2311.6
17.5°	2221.8
20°	2070.4
22.5°	1892.1
25°	1701.4
27.5°	1486.1
30°	1244.6
32.5°	1025.7
35°	831.7
37.5°	640.0
40°	459.1
42.5°	299.8
45°	172.0
47.5°	91.1
50°	56.7
52.5°	39.3
55°	28.2
57.5°	20.3
60°	14.1
62.5°	9.2
65°	6.6
67.5°	5.9
70°	5.6
72.5°	4.3
75°	3.3
77.5°	2.9
80°	2.3
82.5°	1.6
85°	1.0
87.5°	0.7
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)