

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P790568

Luminaire Tested: LER6D20D010-EC6DR7020359027-6LBDP1H

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P790568
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D20D010-EC6DR7020359027-6LBDP1H
Description: 6 INCH ROUND DEEP 45° CUTOFF SEMI-SPECULAR CLEAR TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3272.1 lumens
Efficiency: N/A
Efficacy: 141.6 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 23.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P790568
CATALOG NUMBER: LER6D20D010-EC6DR7020359027-6LBDP1H

Luminous Intensity Polar Plot





TEST NUMBER: P790568
 CATALOG NUMBER: LER6D20D010-EC6DR7020359027-6LBDP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	401938
5°	389993
10°	379126
15°	374151
20°	349377
25°	262474
30°	185549
35°	65731
40°	34559
45°	36806
50°	38109
55°	38841
60°	39072
65°	38237
70°	36099
75°	33434
80°	29699
85°	24070

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 39084 cd/sqm



TEST NUMBER: P790568

CATALOG NUMBER: LER6D20D010-EC6DR7020359027-6LBDP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	335.4	10.3
10°-20°	920.0	28.1
20°-30°	1013.2	31.0
30°-40°	387.1	11.8
40°-50°	182.8	5.6
50°-60°	181.7	5.6
60°-70°	145.5	4.4
70°-80°	83.6	2.6
80°-90°	22.7	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2268.6	69.3
0°-40°	2655.7	81.2
0°-60°	3020.2	92.3
0°-90°	3272.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3272.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3679	
5°	3556	335
15°	3308	920
25°	2177	1013
35°	493	387
45°	238	183
55°	204	182
65°	148	145
75°	79	84
85°	19	23
90°	0	



TEST NUMBER: P790568

CATALOG NUMBER: LER6D20D010-EC6DR7020359027-6LBDP1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	3678.7
2.5°	3640.3
5°	3555.8
7.5°	3485.4
10°	3417.2
12.5°	3359.6
15°	3307.7
17.5°	3182.5
20°	3004.8
22.5°	2621.6
25°	2177.2
27.5°	1895.3
30°	1470.7
32.5°	950.0
35°	492.8
37.5°	266.2
40°	242.3
42.5°	240.6
45°	238.2
47.5°	233.0
50°	224.2
52.5°	214.3
55°	203.9
57.5°	192.2
60°	178.8
62.5°	163.7
65°	147.9
67.5°	130.5
70°	113.0
72.5°	95.5
75°	79.2
77.5°	62.3
80°	47.2
82.5°	33.2
85°	19.2
87.5°	7.6
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)