

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P791057

Luminaire Tested: LER6D25D010-EC6DR6020359030-6LBDP1LI

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P791057
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D25D010-EC6DR6020359030-6LBDDP1LI
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR CLEAR TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5211.2 lumens
Efficiency: N/A
Efficacy: 207.6 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 25.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P791057
CATALOG NUMBER: LER6D25D010-EC6DR6020359030-6LBDP1LI

Luminous Intensity Polar Plot





TEST NUMBER: P791057

CATALOG NUMBER: LER6D25D010-EC6DR6020359030-6LBDP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93																			
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86																			
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																			
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70																			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66																			
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62																			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59																			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55																			
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	676204
5°	692837
10°	701203
15°	667990
20°	588969
25°	476377
30°	322221
35°	161473
40°	26187
45°	25635
50°	26143
55°	26535
60°	27271
65°	27896
70°	28559
75°	28917
80°	27874
85°	23192

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 75°
 Luminance: 28917 cd/sqm



TEST NUMBER: P791057

CATALOG NUMBER: LER6D25D010-EC6DR6020359030-6LBDP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	603.7	11.6
10°-20°	1633.5	31.3
20°-30°	1757.5	33.7
30°-40°	763.9	14.7
40°-50°	128.3	2.5
50°-60°	124.7	2.4
60°-70°	106.7	2.0
70°-80°	71.4	1.4
80°-90°	21.3	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3994.7	76.7
0°-40°	4758.7	91.3
0°-60°	5011.7	96.2
0°-90°	5211.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5211.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6189	
5°	6317	604
15°	5905	1633
25°	3952	1757
35°	1211	764
45°	166	128
55°	139	125
65°	108	107
75°	68	71
85°	18	21
90°	0	



TEST NUMBER: P791057

CATALOG NUMBER: LER6D25D010-EC6DR6020359030-6LBDP1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	6188.9
2.5°	6362.9
5°	6317.0
7.5°	6331.5
10°	6320.2
12.5°	6189.7
15°	5905.4
17.5°	5523.7
20°	5065.4
22.5°	4574.9
25°	3951.5
27.5°	3160.5
30°	2554.0
32.5°	1968.5
35°	1210.6
37.5°	517.9
40°	183.6
42.5°	169.1
45°	165.9
47.5°	160.3
50°	153.8
52.5°	146.6
55°	139.3
57.5°	132.1
60°	124.8
62.5°	116.8
65°	107.9
67.5°	99.1
70°	89.4
72.5°	78.9
75°	68.5
77.5°	56.4
80°	44.3
82.5°	31.4
85°	18.5
87.5°	6.4
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)