

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P791127

Luminaire Tested: LER6D25D010-EC6DR6520359050-6LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P791127
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D25D010-EC6DR6520359050-6LBDDP1B
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3463.0 lumens
Efficiency: N/A
Efficacy: 138.0 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 25.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P791127

CATALOG NUMBER: LER6D25D010-EC6DR6520359050-6LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P791127

CATALOG NUMBER: LER6D25D010-EC6DR6520359050-6LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93			
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87			
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80			
4	97	89	84	79	95	88	83	79	86	82	78	84	80	77	82	79	76	75			
5	92	83	78	73	90	83	77	73	81	76	72	79	75	72	77	74	71	69			
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65			
7	83	73	67	63	81	73	67	63	71	66	62	70	66	62	69	65	62	60			
8	79	69	63	59	77	68	63	59	67	62	58	66	62	58	65	61	58	57			
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	58	54	53			
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	372535
5°	372851
10°	385971
15°	386616
20°	355946
25°	303282
30°	232166
35°	164021
40°	96817
45°	39309
50°	14244
55°	7943
60°	4545
65°	2508
70°	2620
75°	2026
80°	2139
85°	1880

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 39309 cd/sqm



TEST NUMBER: P791127

CATALOG NUMBER: LER6D25D010-EC6DR6520359050-6LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	328.3	9.5
10°-20°	947.1	27.3
20°-30°	1136.3	32.8
30°-40°	763.6	22.1
40°-50°	228.6	6.6
50°-60°	40.3	1.2
60°-70°	11.5	0.3
70°-80°	5.6	0.2
80°-90°	1.8	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2411.7	69.6
0°-40°	3175.3	91.7
0°-60°	3444.2	99.5
0°-90°	3463.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3463.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3410	
5°	3400	328
15°	3418	947
25°	2516	1136
35°	1230	764
45°	254	229
55°	42	40
65°	10	11
75°	5	6
85°	2	2
90°	0	



TEST NUMBER: P791127

CATALOG NUMBER: LER6D25D010-EC6DR6520359050-6LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	3409.6
2.5°	3424.2
5°	3399.5
7.5°	3450.8
10°	3478.9
12.5°	3472.1
15°	3417.9
17.5°	3285.1
20°	3061.3
22.5°	2797.7
25°	2515.7
27.5°	2197.3
30°	1840.2
32.5°	1516.6
35°	1229.7
37.5°	946.3
40°	678.8
42.5°	443.3
45°	254.4
47.5°	134.7
50°	83.8
52.5°	58.1
55°	41.7
57.5°	30.0
60°	20.8
62.5°	13.6
65°	9.7
67.5°	8.7
70°	8.2
72.5°	6.3
75°	4.8
77.5°	4.4
80°	3.4
82.5°	2.4
85°	1.5
87.5°	1.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)