

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P791334

Luminaire Tested: LER6D30D010-EC6DR3020359024-6LBS1MW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P791334
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-16)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D30D010-EC6DR3020359024-6LBS1MW
Description: 6 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 30° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4741.7 lumens
Efficiency: N/A
Efficacy: 163.5 lumens/watt
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.49
Luminous Opening: Rectangular (W 0.38' x L: 0.38' x H: 0')
CIE Type: Direct

Input Watts (W): 29
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P791334

CATALOG NUMBER: LER6D30D010-EC6DR3020359024-6LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P791334

CATALOG NUMBER: LER6D30D010-EC6DR3020359024-6LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96																			
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92																			
3	107	102	98	95	105	101	97	94	98	95	93	96	93	91	94	92	90	89																			
4	103	98	93	90	102	96	93	90	94	91	89	93	90	88	91	89	87	85																			
5	100	94	89	86	98	93	89	86	91	88	85	90	86	84	88	86	83	82																			
6	97	90	85	82	95	89	85	82	88	84	81	87	83	81	85	83	80	79																			
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77																			
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74																			
9	88	81	76	73	87	80	76	73	80	76	73	79	75	73	78	75	73	72																			
10	85	78	74	71	85	78	74	71	77	73	71	76	73	71	76	73	70	69																			

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1167057	1167057	1167057
5°	1133558	1132229	1133612
10°	981828	974910	981602
15°	640597	637158	633948
20°	318541	330491	318109
25°	160459	180939	157173
30°	64247	70001	55974
35°	29799	28537	23921
40°	12870	14289	12120
45°	9071	11269	9158
50°	3120	8205	3299
55°	1802	3403	1895
60°	1255	1485	1255
65°	815	815	815
70°	492	336	492
75°	0	207	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 22.5°
 Vertical Angle: 45°
 Luminance: 11269 cd/sqm



TEST NUMBER: P791334

CATALOG NUMBER: LER6D30D010-EC6DR3020359024-6LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1340.7	28.3
10°-20°	2159.3	45.5
20°-30°	933.1	19.7
30°-40°	212.7	4.5
40°-50°	73.0	1.5
50°-60°	17.8	0.4
60°-70°	4.6	0.1
70°-80°	0.5	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4433.1	93.5
0°-40°	4645.8	98.0
0°-60°	4736.7	99.9
0°-90°	4741.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4741.7	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	15247	15247	15247	15247	15247	
5°	14753	14739	14736	14766	14754	1342
15°	8084	7987	8040	8014	8000	2165
25°	1900	1972	2142	1922	1861	909
35°	319	326	305	303	256	216
45°	84	104	104	104	85	59
55°	14	14	26	15	14	13
65°	4	4	4	4	4	4
75°	0	0	1	0	0	1
85°	0	0	0	0	0	0
90°	0	0	0	0	0	0



TEST NUMBER: P791334

CATALOG NUMBER: LER6D30D010-EC6DR3020359024-6LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	15247.0	15247.0	15247.0	15247.0	15247.0
2.5°	15146.0	15135.5	15141.5	15149.0	15152.0
5°	14753.0	14738.7	14735.7	14766.4	14753.7
7.5°	13960.2	13940.0	13909.3	13978.9	14044.1
10°	12632.2	12609.8	12543.2	12576.1	12629.3
12.5°	10671.7	10599.1	10597.6	10702.4	10688.2
15°	8083.9	7986.6	8040.5	8014.3	8000.0
17.5°	5436.2	5398.7	5470.6	5448.9	5355.3
20°	3910.6	3920.3	4057.3	3988.4	3905.3
22.5°	2853.6	2888.8	3051.2	2873.8	2808.7
25°	1899.9	1971.8	2142.4	1921.6	1861.0
27.5°	1168.5	1201.5	1374.4	1153.6	1120.6
30°	726.9	710.4	792.0	679.7	633.3
32.5°	476.8	455.9	482.1	432.7	395.2
35°	318.9	325.6	305.4	303.2	256.0
37.5°	199.1	229.1	202.1	215.6	164.7
40°	128.8	166.2	143.0	157.9	121.3
42.5°	105.5	128.0	117.5	125.0	107.8
45°	83.8	104.1	104.1	104.1	84.6
47.5°	46.4	69.6	89.1	71.1	49.4
50°	26.2	35.2	68.9	36.7	27.7
52.5°	18.0	20.2	47.2	21.0	18.7
55°	13.5	14.2	25.5	15.0	14.2
57.5°	10.5	11.2	13.5	11.2	10.5
60°	8.2	8.2	9.7	9.0	8.2
62.5°	6.0	6.0	6.7	6.0	6.0
65°	4.5	4.5	4.5	4.5	4.5
67.5°	2.2	3.0	3.0	3.0	3.0
70°	2.2	1.5	1.5	1.5	2.2
72.5°	1.5	0.7	0.7	0.7	0.7
75°	0.0	0.0	0.7	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report





— 0°-180° - - 45°-225° - - - - 90°-270°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)