

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P791667

Luminaire Tested: LER6D30D010-EC6DR6520359024-6LBS1B

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P791667
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D30D010-EC6DR6520359024-6LBS1B
Description: 6 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4156.0 lumens
Efficiency: N/A
Efficacy: 143.3 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct


Input Watts (W): 29
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P791667
CATALOG NUMBER: LER6D30D010-EC6DR6520359024-6LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P791667

CATALOG NUMBER: LER6D30D010-EC6DR6520359024-6LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100																
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	93			93																
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85			85																
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80	78			78																
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72			72																
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68	66			66																
6	85	75	69	64	83	74	68	64	73	67	63	71	67	63	70	66	62	61			61																
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58	56			56																
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54	52			52																
9	72	61	55	51	71	61	55	51	60	54	51	59	54	50	58	54	50	49			49																
10	68	58	52	47	67	57	51	47	57	51	47	56	51	47	55	50	47	46			46																

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	220387
5°	219828
10°	219641
15°	212870
20°	193790
25°	168876
30°	140462
35°	111296
40°	80327
45°	50747
50°	26449
55°	14062
60°	7382
65°	4063
70°	1708
75°	1873
80°	1312
85°	1139

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 50747 cd/sqm



TEST NUMBER: P791667

CATALOG NUMBER: LER6D30D010-EC6DR6520359024-6LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	356.8	8.6
10°-20°	977.2	23.5
20°-30°	1194.5	28.7
30°-40°	969.2	23.3
40°-50°	483.0	11.6
50°-60°	134.7	3.2
60°-70°	30.6	0.7
70°-80°	7.9	0.2
80°-90°	2.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2528.5	60.8
0°-40°	3497.7	84.2
0°-60°	4115.3	99.0
0°-90°	4156.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4156.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3774	
5°	3750	357
15°	3521	977
25°	2621	1194
35°	1561	969
45°	614	483
55°	138	135
65°	29	31
75°	8	8
85°	2	2
90°	0	



TEST NUMBER: P791667

CATALOG NUMBER: LER6D30D010-EC6DR6520359024-6LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	3773.5
2.5°	3770.7
5°	3749.6
7.5°	3737.4
10°	3703.6
12.5°	3634.8
15°	3520.6
17.5°	3342.1
20°	3118.0
22.5°	2876.3
25°	2620.6
27.5°	2347.3
30°	2082.8
32.5°	1821.6
35°	1561.0
37.5°	1300.9
40°	1053.6
42.5°	821.8
45°	614.4
47.5°	428.1
50°	291.1
52.5°	200.7
55°	138.1
57.5°	93.2
60°	63.2
62.5°	43.8
65°	29.4
67.5°	15.0
70°	10.0
72.5°	9.4
75°	8.3
77.5°	5.5
80°	3.9
82.5°	2.8
85°	1.7
87.5°	1.1
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)