

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P791817

Luminaire Tested: LER6D35BD010-EC6DR3020359027-6LBDP1LI

Issue Date: 2/2/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P791817  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-16)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/2/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LER6D35BD010-EC6DR3020359027-6LBDP1LI  
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR CLEAR TRIM, WITH 30° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 3784.9 lumens  
Efficiency: N/A  
Efficacy: 122.9 lumens/watt  
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.49  
Luminous Opening: Rectangular (W 0.38' x L: 0.38' x H: 0')  
CIE Type: Direct

Input Watts (W): 30.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT




Downlight

TEST NUMBER: P791817

CATALOG NUMBER: LER6D35BD010-EC6DR3020359027-6LBDP1LI

### Luminous Intensity Polar Plot





TEST NUMBER: P791817

CATALOG NUMBER: LER6D35BD010-EC6DR3020359027-6LBDP1LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0													
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						100													
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96						96													
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92						92													
3	107	102	98	95	105	101	97	94	98	95	93	96	93	91	94	92	90	89						89													
4	103	98	93	90	102	96	93	90	94	91	89	93	90	88	91	89	87	85						85													
5	100	94	89	86	98	93	89	86	91	88	85	90	86	84	88	86	83	82						82													
6	97	90	85	82	95	89	85	82	88	84	81	87	83	81	85	83	80	79						79													
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77						77													
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74						74													
9	88	81	76	73	87	80	76	73	80	76	73	79	75	73	78	75	73	72						72													
10	85	78	74	71	85	78	74	71	77	73	71	76	73	71	76	73	70	69						69													

**AVERAGE LUMINANCE (cd/sqm):**

	0°	45°	90°
0°	931548	931548	931548
5°	904803	903750	904849
10°	783701	778175	783514
15°	511327	508577	506018
20°	254256	263795	253914
25°	128078	144429	125451
30°	51281	55877	44678
35°	23781	22781	19100
40°	10272	11401	9672
45°	7242	8995	7307
50°	2489	6549	2632
55°	1441	2709	1521
60°	1010	1194	1010
65°	652	652	652
70°	403	269	403
75°	0	177	0
80°	0	0	0
85°	0	0	0

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 22.5°  
 Vertical Angle: 45°  
 Luminance: 8995 cd/sqm



TEST NUMBER: P791817

CATALOG NUMBER: LER6D35BD010-EC6DR3020359027-6LBDP1LI

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	1070.2	28.3
10°-20°	1723.5	45.5
20°-30°	744.8	19.7
30°-40°	169.8	4.5
40°-50°	58.3	1.5
50°-60°	14.3	0.4
60°-70°	3.7	0.1
70°-80°	0.4	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3538.5	93.5
0°-40°	3708.3	98.0
0°-60°	3780.8	99.9
0°-90°	3784.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3784.9	100.0

**CANDELA DISTRIBUTION:**

	0°	22.5°	45°	67.5°	90°	Flux
0°	12170	12170	12170	12170	12170	
5°	11776	11764	11762	11787	11776	1071
15°	6453	6375	6418	6397	6386	1728
25°	1516	1574	1710	1534	1485	726
35°	254	260	244	242	204	173
45°	67	83	83	83	68	47
55°	11	11	20	12	11	10
65°	4	4	4	4	4	4
75°	0	0	1	0	0	1
85°	0	0	0	0	0	0
90°	0	0	0	0	0	0



TEST NUMBER: P791817

CATALOG NUMBER: LER6D35BD010-EC6DR3020359027-6LBDP1LI

**CANDELA DISTRIBUTION (FULL):**

	0°	22.5°	45°	67.5°	90°
0°	12170.2	12170.2	12170.2	12170.2	12170.2
2.5°	12089.5	12081.2	12085.9	12091.9	12094.3
5°	11775.8	11764.5	11762.1	11786.6	11776.4
7.5°	11143.1	11126.9	11102.4	11158.0	11210.0
10°	10083.1	10065.1	10012.0	10038.3	10080.7
12.5°	8518.2	8460.2	8459.0	8542.7	8531.3
15°	6452.6	6374.9	6417.9	6397.0	6385.6
17.5°	4339.2	4309.3	4366.6	4349.3	4274.6
20°	3121.4	3129.2	3238.5	3183.6	3117.2
22.5°	2277.7	2305.8	2435.5	2293.9	2241.9
25°	1516.5	1573.9	1710.1	1533.8	1485.4
27.5°	932.7	959.0	1097.0	920.8	894.5
30°	580.2	567.0	632.2	542.5	505.5
32.5°	380.6	363.9	384.8	345.4	315.5
35°	254.5	259.9	243.8	242.0	204.4
37.5°	158.9	182.8	161.3	172.1	131.5
40°	102.8	132.6	114.1	126.1	96.8
42.5°	84.2	102.2	93.8	99.8	86.0
45°	66.9	83.1	83.1	83.1	67.5
47.5°	37.0	55.6	71.1	56.8	39.4
50°	20.9	28.1	55.0	29.3	22.1
52.5°	14.3	16.1	37.6	16.7	14.9
55°	10.8	11.4	20.3	12.0	11.4
57.5°	8.4	9.0	10.8	9.0	8.4
60°	6.6	6.6	7.8	7.2	6.6
62.5°	4.8	4.8	5.4	4.8	4.8
65°	3.6	3.6	3.6	3.6	3.6
67.5°	1.8	2.4	2.4	2.4	2.4
70°	1.8	1.2	1.2	1.2	1.8
72.5°	1.2	0.6	0.6	0.6	0.6
75°	0.0	0.0	0.6	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report







— 0°-180°    - - 45°-225°    - - - - 90°-270°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)