

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P792106

Luminaire Tested: LER6D35BD010-EC6DR6020359027-6LBDP1MW

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P792106
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D35BD010-EC6DR6020359027-6LBDP1MW
Description: 6 INCH ROUND DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3352.3 lumens
Efficiency: N/A
Efficacy: 108.8 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 30.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P792106
CATALOG NUMBER: LER6D35BD010-EC6DR6020359027-6LBDP1MW

Luminous Intensity Polar Plot





TEST NUMBER: P792106

CATALOG NUMBER: LER6D35BD010-EC6DR6020359027-6LBDP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93																			
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86																			
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																			
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70																			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66																			
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62																			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59																			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55																			
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	435000
5°	445699
10°	451085
15°	429713
20°	378875
25°	306441
30°	207287
35°	103865
40°	16845
45°	16487
50°	16828
55°	17068
60°	17547
65°	17942
70°	18369
75°	18575
80°	17932
85°	14918

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 75°
 Luminance: 18575 cd/sqm



TEST NUMBER: P792106

CATALOG NUMBER: LER6D35BD010-EC6DR6020359027-6LBDP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	388.4	11.6
10°-20°	1050.8	31.3
20°-30°	1130.6	33.7
30°-40°	491.4	14.7
40°-50°	82.5	2.5
50°-60°	80.3	2.4
60°-70°	68.6	2.0
70°-80°	45.9	1.4
80°-90°	13.7	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2569.8	76.7
0°-40°	3061.2	91.3
0°-60°	3224.0	96.2
0°-90°	3352.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3352.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3981	
5°	4064	388
15°	3799	1051
25°	2542	1131
35°	779	491
45°	107	83
55°	90	80
65°	69	69
75°	44	46
85°	12	14
90°	0	



TEST NUMBER: P792106

CATALOG NUMBER: LER6D35BD010-EC6DR6020359027-6LBDP1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	3981.3
2.5°	4093.2
5°	4063.7
7.5°	4073.0
10°	4065.8
12.5°	3981.8
15°	3798.9
17.5°	3553.3
20°	3258.5
22.5°	2943.0
25°	2541.9
27.5°	2033.1
30°	1643.0
32.5°	1266.3
35°	778.7
37.5°	333.2
40°	118.1
42.5°	108.8
45°	106.7
47.5°	103.1
50°	99.0
52.5°	94.3
55°	89.6
57.5°	85.0
60°	80.3
62.5°	75.1
65°	69.4
67.5°	63.7
70°	57.5
72.5°	50.8
75°	44.0
77.5°	36.3
80°	28.5
82.5°	20.2
85°	11.9
87.5°	4.1
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)