

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P792167

Luminaire Tested: LER6D35BD010-EC6DR6520359035-6LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P792167
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D35BD010-EC6DR6520359035-6LBDP1B
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2508.3 lumens
Efficiency: N/A
Efficacy: 81.4 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 30.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P792167

CATALOG NUMBER: LER6D35BD010-EC6DR6520359035-6LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P792167

CATALOG NUMBER: LER6D35BD010-EC6DR6520359035-6LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93			
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87			
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80			
4	97	89	84	79	95	88	83	79	86	82	78	84	80	77	82	79	76	75			
5	92	83	78	73	90	83	77	73	81	76	72	79	75	72	77	74	71	69			
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65			
7	83	73	67	63	81	73	67	63	71	66	62	70	66	62	69	65	62	60			
8	79	69	63	59	77	68	63	59	67	62	58	66	62	58	65	61	58	57			
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	58	54	53			
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	269830
5°	270049
10°	279562
15°	280016
20°	257800
25°	219665
30°	168163
35°	118804
40°	70131
45°	28462
50°	10318
55°	5753
60°	3300
65°	1810
70°	1917
75°	1478
80°	1573
85°	1379

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 28462 cd/sqm



TEST NUMBER: P792167

CATALOG NUMBER: LER6D35BD010-EC6DR6520359035-6LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	237.8	9.5
10°-20°	685.9	27.3
20°-30°	823.0	32.8
30°-40°	553.1	22.0
40°-50°	165.6	6.6
50°-60°	29.2	1.2
60°-70°	8.3	0.3
70°-80°	4.1	0.2
80°-90°	1.3	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1746.7	69.6
0°-40°	2299.8	91.7
0°-60°	2494.6	99.5
0°-90°	2508.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2508.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2470	
5°	2462	238
15°	2476	686
25°	1822	823
35°	891	553
45°	184	166
55°	30	29
65°	7	8
75°	4	4
85°	1	1
90°	0	



TEST NUMBER: P792167

CATALOG NUMBER: LER6D35BD010-EC6DR6520359035-6LBDP1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	2469.6
2.5°	2480.1
5°	2462.2
7.5°	2499.4
10°	2519.8
12.5°	2514.8
15°	2475.5
17.5°	2379.4
20°	2217.2
22.5°	2026.3
25°	1822.1
27.5°	1591.5
30°	1332.9
32.5°	1098.4
35°	890.7
37.5°	685.4
40°	491.7
42.5°	321.1
45°	184.2
47.5°	97.6
50°	60.7
52.5°	42.1
55°	30.2
57.5°	21.8
60°	15.1
62.5°	9.8
65°	7.0
67.5°	6.3
70°	6.0
72.5°	4.6
75°	3.5
77.5°	3.2
80°	2.5
82.5°	1.8
85°	1.1
87.5°	0.7
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)