

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P792215

Luminaire Tested: LER6D35BD010-EC6DR7020359035-6LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P792215
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D35BD010-EC6DR7020359035-6LBDP1B
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2256.9 lumens
Efficiency: N/A
Efficacy: 73.3 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 30.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P792215

CATALOG NUMBER: LER6D35BD010-EC6DR7020359035-6LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P792215

CATALOG NUMBER: LER6D35BD010-EC6DR7020359035-6LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	277238
5°	269008
10°	261500
15°	258072
20°	240987
25°	181039
30°	127980
35°	45337
40°	23833
45°	25387
50°	26296
55°	26783
60°	26944
65°	26370
70°	24886
75°	23049
80°	20449
85°	16673

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 26964 cd/sqm



TEST NUMBER: P792215

CATALOG NUMBER: LER6D35BD010-EC6DR7020359035-6LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	231.3	10.3
10°-20°	634.5	28.1
20°-30°	698.9	31.0
30°-40°	267.0	11.8
40°-50°	126.1	5.6
50°-60°	125.3	5.6
60°-70°	100.3	4.4
70°-80°	57.7	2.6
80°-90°	15.7	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1564.8	69.3
0°-40°	1831.8	81.2
0°-60°	2083.2	92.3
0°-90°	2256.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2256.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2537	
5°	2453	231
15°	2282	635
25°	1502	699
35°	340	267
45°	164	126
55°	141	125
65°	102	100
75°	55	58
85°	13	16
90°	0	



TEST NUMBER: P792215

CATALOG NUMBER: LER6D35BD010-EC6DR7020359035-6LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	2537.4
2.5°	2510.9
5°	2452.7
7.5°	2404.0
10°	2357.0
12.5°	2317.3
15°	2281.5
17.5°	2195.1
20°	2072.6
22.5°	1808.3
25°	1501.7
27.5°	1307.3
30°	1014.4
32.5°	655.2
35°	339.9
37.5°	183.6
40°	167.1
42.5°	165.9
45°	164.3
47.5°	160.7
50°	154.7
52.5°	147.8
55°	140.6
57.5°	132.6
60°	123.3
62.5°	112.9
65°	102.0
67.5°	90.0
70°	77.9
72.5°	65.9
75°	54.6
77.5°	43.0
80°	32.5
82.5°	22.9
85°	13.3
87.5°	5.2
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)