

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P792218

Luminaire Tested: LER6D35BD010-EC6DR7020359035-6LBDP1MW

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P792218
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D35BD010-EC6DR7020359035-6LBDP1MW
Description: 6 INCH ROUND DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3029.9 lumens
Efficiency: N/A
Efficacy: 98.4 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 30.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P792218

CATALOG NUMBER: LER6D35BD010-EC6DR7020359035-6LBDP1MW

Luminous Intensity Polar Plot





TEST NUMBER: P792218
 CATALOG NUMBER: LER6D35BD010-EC6DR7020359035-6LBDP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	372197
5°	361137
10°	351067
15°	346460
20°	323529
25°	243053
30°	171809
35°	60863
40°	32006
45°	34087
50°	35288
55°	35965
60°	36187
65°	35419
70°	33415
75°	30986
80°	27496
85°	22315

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 36197 cd/sqm



TEST NUMBER: P792218

CATALOG NUMBER: LER6D35BD010-EC6DR7020359035-6LBDP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	310.6	10.3
10°-20°	851.9	28.1
20°-30°	938.2	31.0
30°-40°	358.5	11.8
40°-50°	169.2	5.6
50°-60°	168.3	5.6
60°-70°	134.7	4.4
70°-80°	77.5	2.6
80°-90°	21.0	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2100.7	69.3
0°-40°	2459.2	81.2
0°-60°	2796.7	92.3
0°-90°	3029.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3029.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3406	
5°	3293	311
15°	3063	852
25°	2016	938
35°	456	358
45°	221	169
55°	189	168
65°	137	135
75°	73	77
85°	18	21
90°	0	



TEST NUMBER: P792218

CATALOG NUMBER: LER6D35BD010-EC6DR7020359035-6LBDP1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	3406.5
2.5°	3370.9
5°	3292.7
7.5°	3227.4
10°	3164.3
12.5°	3110.9
15°	3062.9
17.5°	2947.0
20°	2782.5
22.5°	2427.6
25°	2016.1
27.5°	1755.0
30°	1361.8
32.5°	879.7
35°	456.3
37.5°	246.5
40°	224.4
42.5°	222.7
45°	220.6
47.5°	215.7
50°	207.6
52.5°	198.5
55°	188.8
57.5°	178.0
60°	165.6
62.5°	151.6
65°	137.0
67.5°	120.8
70°	104.6
72.5°	88.5
75°	73.4
77.5°	57.7
80°	43.7
82.5°	30.7
85°	17.8
87.5°	7.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)