

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P793072

Luminaire Tested: LER6D45BD010-EC6DR6040509030-6LBDP1H

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P793072
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D45BD010-EC6DR6040509030-6LBDP1H
Description: 6 INCH ROUND DEEP 45° CUTOFF SEMI-SPECULAR CLEAR TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4917.7 lumens
Efficiency: N/A
Efficacy: 127.1 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 38.7
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P793072

CATALOG NUMBER: LER6D45BD010-EC6DR6040509030-6LBDP1H

Luminous Intensity Polar Plot





TEST NUMBER: P793072

CATALOG NUMBER: LER6D45BD010-EC6DR6040509030-6LBDP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93																			
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86																			
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																			
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70																			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66																			
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62																			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59																			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55																			
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	638116
5°	653813
10°	661706
15°	630368
20°	555784
25°	449541
30°	304079
35°	152376
40°	24718
45°	24198
50°	24681
55°	25049
60°	25742
65°	26319
70°	26962
75°	27271
80°	26301
85°	21938

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 75°
 Luminance: 27271 cd/sqm



TEST NUMBER: P793072

CATALOG NUMBER: LER6D45BD010-EC6DR6040509030-6LBDP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	569.7	11.6
10°-20°	1541.5	31.3
20°-30°	1658.5	33.7
30°-40°	720.9	14.7
40°-50°	121.1	2.5
50°-60°	117.7	2.4
60°-70°	100.7	2.0
70°-80°	67.4	1.4
80°-90°	20.2	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3769.7	76.7
0°-40°	4490.6	91.3
0°-60°	4729.5	96.2
0°-90°	4917.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4917.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5840	
5°	5961	570
15°	5573	1541
25°	3729	1658
35°	1142	721
45°	157	121
55°	132	118
65°	102	101
75°	65	67
85°	18	20
90°	0	



TEST NUMBER: P793072

CATALOG NUMBER: LER6D45BD010-EC6DR6040509030-6LBDP1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	5840.3
2.5°	6004.5
5°	5961.2
7.5°	5974.8
10°	5964.2
12.5°	5841.1
15°	5572.8
17.5°	5212.5
20°	4780.0
22.5°	4317.2
25°	3728.9
27.5°	2982.5
30°	2410.2
32.5°	1857.6
35°	1142.4
37.5°	488.7
40°	173.3
42.5°	159.6
45°	156.6
47.5°	151.3
50°	145.2
52.5°	138.3
55°	131.5
57.5°	124.7
60°	117.8
62.5°	110.2
65°	101.8
67.5°	93.5
70°	84.4
72.5°	74.5
75°	64.6
77.5°	53.2
80°	41.8
82.5°	29.6
85°	17.5
87.5°	6.1
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)