

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P793112

Luminaire Tested: LER6D45BD010-EC6DR6540509027-6LBDP1H

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P793112
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D45BD010-EC6DR6540509027-6LBDP1H
Description: 6 INCH ROUND DEEP 45° CUTOFF SEMI-SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4170.9 lumens
Efficiency: N/A
Efficacy: 107.8 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 38.7
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P793112

CATALOG NUMBER: LER6D45BD010-EC6DR6540509027-6LBDP1H

Luminous Intensity Polar Plot





TEST NUMBER: P793112

CATALOG NUMBER: LER6D45BD010-EC6DR6540509027-6LBDP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93		
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87		
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80		
4	97	89	84	79	95	88	83	79	86	82	78	84	80	77	82	79	76	75		
5	92	83	78	73	90	83	77	73	81	76	72	79	75	72	77	74	71	69		
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65		
7	83	73	67	63	81	73	67	63	71	66	62	70	66	62	69	65	62	60		
8	79	69	63	59	77	68	63	59	67	62	58	66	62	58	65	61	58	57		
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	58	54	53		
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	448679
5°	449044
10°	464854
15°	465627
20°	428686
25°	365260
30°	279616
35°	197553
40°	116614
45°	47344
50°	17168
55°	9563
60°	5485
65°	3025
70°	3163
75°	2448
80°	2580
85°	2257

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 47344 cd/sqm



TEST NUMBER: P793112

CATALOG NUMBER: LER6D45BD010-EC6DR6540509027-6LBDP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	395.4	9.5
10°-20°	1140.6	27.3
20°-30°	1368.5	32.8
30°-40°	919.7	22.1
40°-50°	275.3	6.6
50°-60°	48.6	1.2
60°-70°	13.8	0.3
70°-80°	6.8	0.2
80°-90°	2.2	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2904.5	69.6
0°-40°	3824.2	91.7
0°-60°	4148.1	99.5
0°-90°	4170.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4170.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4106	
5°	4094	395
15°	4116	1141
25°	3030	1369
35°	1481	920
45°	306	275
55°	50	49
65°	12	14
75°	6	7
85°	2	2
90°	0	



TEST NUMBER: P793112

CATALOG NUMBER: LER6D45BD010-EC6DR6540509027-6LBDP1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	4106.5
2.5°	4124.0
5°	4094.2
7.5°	4156.1
10°	4189.9
12.5°	4181.8
15°	4116.4
17.5°	3956.5
20°	3686.9
22.5°	3369.5
25°	3029.8
27.5°	2646.4
30°	2216.3
32.5°	1826.5
35°	1481.1
37.5°	1139.7
40°	817.6
42.5°	534.0
45°	306.4
47.5°	162.2
50°	101.0
52.5°	70.0
55°	50.2
57.5°	36.2
60°	25.1
62.5°	16.3
65°	11.7
67.5°	10.5
70°	9.9
72.5°	7.6
75°	5.8
77.5°	5.3
80°	4.1
82.5°	2.9
85°	1.8
87.5°	1.2
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)