

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P793143

Luminaire Tested: LER6D45BD010-EC6DR6540509050-6LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P793143
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D45BD010-EC6DR6540509050-6LBDP1B
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3409.8 lumens
Efficiency: N/A
Efficacy: 88.1 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 38.7
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P793143

CATALOG NUMBER: LER6D45BD010-EC6DR6540509050-6LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P793143

CATALOG NUMBER: LER6D45BD010-EC6DR6540509050-6LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93			
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87			
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80			
4	97	89	84	79	95	88	83	79	86	82	78	84	80	77	82	79	76	75			
5	92	83	78	73	90	83	77	73	81	76	72	79	75	72	77	74	71	69			
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65			
7	83	73	67	63	81	73	67	63	71	66	62	70	66	62	69	65	62	60			
8	79	69	63	59	77	68	63	59	67	62	58	66	62	58	65	61	58	57			
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	58	54	53			
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	366810
5°	367115
10°	380035
15°	380666
20°	350470
25°	298617
30°	228596
35°	161500
40°	95334
45°	38707
50°	14023
55°	7810
60°	4480
65°	2456
70°	2588
75°	2026
80°	2076
85°	1755

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 38707 cd/sqm



TEST NUMBER: P793143

CATALOG NUMBER: LER6D45BD010-EC6DR6540509050-6LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	323.3	9.5
10°-20°	932.5	27.3
20°-30°	1118.8	32.8
30°-40°	751.9	22.1
40°-50°	225.1	6.6
50°-60°	39.7	1.2
60°-70°	11.3	0.3
70°-80°	5.5	0.2
80°-90°	1.8	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2374.6	69.6
0°-40°	3126.4	91.7
0°-60°	3391.2	99.5
0°-90°	3409.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3409.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3357	
5°	3347	323
15°	3365	932
25°	2477	1119
35°	1211	752
45°	250	225
55°	41	40
65°	10	11
75°	5	6
85°	1	2
90°	0	



TEST NUMBER: P793143

CATALOG NUMBER: LER6D45BD010-EC6DR6540509050-6LBDP1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	3357.2
2.5°	3371.5
5°	3347.2
7.5°	3397.8
10°	3425.4
12.5°	3418.8
15°	3365.3
17.5°	3234.6
20°	3014.2
22.5°	2754.7
25°	2477.0
27.5°	2163.6
30°	1811.9
32.5°	1493.3
35°	1210.8
37.5°	931.7
40°	668.4
42.5°	436.5
45°	250.5
47.5°	132.6
50°	82.5
52.5°	57.2
55°	41.0
57.5°	29.6
60°	20.5
62.5°	13.4
65°	9.5
67.5°	8.6
70°	8.1
72.5°	6.2
75°	4.8
77.5°	4.3
80°	3.3
82.5°	2.4
85°	1.4
87.5°	1.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)