

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P793665

Luminaire Tested: LER6D50D010-EC6DR7040509040-6LBDP1LI

Issue Date: 2/5/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P793665  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/5/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LER6D50D010-EC6DR7040509040-6LBDDP1LI  
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR CLEAR TRIM, WITH 70° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 6456.5 lumens  
Efficiency: N/A  
Efficacy: 137.4 lumens/watt  
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82  
Luminous Opening: Circular (Dia: 0.35' x H: 0')  
CIE Type: Direct


Input Watts (W): 47  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



Downlight

TEST NUMBER: P793665  
CATALOG NUMBER: LER6D50D010-EC6DR7040509040-6LBDP1LI

### Luminous Intensity Polar Plot





TEST NUMBER: P793665

CATALOG NUMBER: LER6D50D010-EC6DR7040509040-6LBDP1LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	793124
5°	769556
10°	748100
15°	738291
20°	689405
25°	517920
30°	366126
35°	129688
40°	68191
45°	72639
50°	75216
55°	76634
60°	77094
65°	75466
70°	71239
75°	65982
80°	58579
85°	47512

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 57.5°  
 Luminance: 77131 cd/sqm



TEST NUMBER: P793665

CATALOG NUMBER: LER6D50D010-EC6DR7040509040-6LBDP1LI

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	661.8	10.3
10°-20°	1815.3	28.1
20°-30°	1999.3	31.0
30°-40°	763.9	11.8
40°-50°	360.7	5.6
50°-60°	358.6	5.6
60°-70°	287.1	4.4
70°-80°	165.0	2.6
80°-90°	44.8	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4476.4	69.3
0°-40°	5240.3	81.2
0°-60°	5959.6	92.3
0°-90°	6456.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6456.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	7259	
5°	7016	662
15°	6527	1815
25°	4296	1999
35°	972	764
45°	470	361
55°	402	359
65°	292	287
75°	156	165
85°	38	45
90°	0	



TEST NUMBER: P793665

CATALOG NUMBER: LER6D50D010-EC6DR7040509040-6LBDP1LI

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	7259.0
2.5°	7183.1
5°	7016.5
7.5°	6877.4
10°	6742.9
12.5°	6629.2
15°	6526.9
17.5°	6279.8
20°	5929.2
22.5°	5173.0
25°	4296.1
27.5°	3739.8
30°	2902.0
32.5°	1874.5
35°	972.3
37.5°	525.2
40°	478.1
42.5°	474.7
45°	470.1
47.5°	459.7
50°	442.5
52.5°	422.9
55°	402.3
57.5°	379.3
60°	352.8
62.5°	323.0
65°	291.9
67.5°	257.4
70°	223.0
72.5°	188.5
75°	156.3
77.5°	123.0
80°	93.1
82.5°	65.5
85°	37.9
87.5°	14.9
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)