

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P793671

Luminaire Tested: LER6D50D010-EC6DR7040509050-6LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P793671
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D50D010-EC6DR7040509050-6LBDDP1B
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3603.2 lumens
Efficiency: N/A
Efficacy: 76.7 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 47
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P793671
CATALOG NUMBER: LER6D50D010-EC6DR7040509050-6LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P793671

CATALOG NUMBER: LER6D50D010-EC6DR7040509050-6LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	442615
5°	429467
10°	417502
15°	412022
20°	384747
25°	289033
30°	204322
35°	72373
40°	38054
45°	40530
50°	41968
55°	42765
60°	43027
65°	42115
70°	39740
75°	36812
80°	32719
85°	26577

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 43050 cd/sqm



TEST NUMBER: P793671

CATALOG NUMBER: LER6D50D010-EC6DR7040509050-6LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	369.3	10.3
10°-20°	1013.1	28.1
20°-30°	1115.8	31.0
30°-40°	426.3	11.8
40°-50°	201.3	5.6
50°-60°	200.1	5.6
60°-70°	160.2	4.4
70°-80°	92.1	2.6
80°-90°	25.1	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2498.2	69.3
0°-40°	2924.5	81.2
0°-60°	3325.9	92.3
0°-90°	3603.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3603.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4051	
5°	3916	369
15°	3642	1013
25°	2398	1116
35°	543	426
45°	262	201
55°	224	200
65°	163	160
75°	87	92
85°	21	25
90°	0	



TEST NUMBER: P793671

CATALOG NUMBER: LER6D50D010-EC6DR7040509050-6LBDP1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	4051.0
2.5°	4008.7
5°	3915.7
7.5°	3838.1
10°	3763.1
12.5°	3699.6
15°	3642.5
17.5°	3504.6
20°	3309.0
22.5°	2886.9
25°	2397.5
27.5°	2087.1
30°	1619.5
32.5°	1046.1
35°	542.6
37.5°	293.1
40°	266.8
42.5°	264.9
45°	262.3
47.5°	256.6
50°	246.9
52.5°	236.0
55°	224.5
57.5°	211.7
60°	196.9
62.5°	180.2
65°	162.9
67.5°	143.7
70°	124.4
72.5°	105.2
75°	87.2
77.5°	68.6
80°	52.0
82.5°	36.6
85°	21.2
87.5°	8.3
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)