

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P793756

Luminaire Tested: LER6D55D010-EC6DR3055659035-6LBS1H

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P793756
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-16)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D55D010-EC6DR3055659035-6LBS1H
Description: 6 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 30° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6763.4 lumens
Efficiency: N/A
Efficacy: 116.2 lumens/watt
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.49
Luminous Opening: Rectangular (W 0.38' x L: 0.38' x H: 0')
CIE Type: Direct


Input Watts (W): 58.2
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P793756
CATALOG NUMBER: LER6D55D010-EC6DR3055659035-6LBS1H

Luminous Intensity Polar Plot





TEST NUMBER: P793756

CATALOG NUMBER: LER6D55D010-EC6DR3055659035-6LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96																			
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92																			
3	107	102	98	95	105	101	97	94	98	95	93	96	93	91	94	92	90	89																			
4	103	98	93	90	102	96	93	90	94	91	89	93	90	88	91	89	87	85																			
5	100	94	89	86	98	93	89	86	91	88	85	90	86	84	88	86	83	82																			
6	97	90	85	82	95	89	85	82	88	84	81	87	83	81	85	83	80	79																			
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77																			
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74																			
9	88	81	76	73	87	80	76	73	80	76	73	79	75	73	78	75	73	72																			
10	85	78	74	71	85	78	74	71	77	73	71	76	73	71	76	73	70	69																			

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1664650	1664650	1664650
5°	1616855	1614973	1616940
10°	1400442	1390571	1400116
15°	913718	908813	904248
20°	454352	471401	453741
25°	228868	258090	224181
30°	91637	99848	79838
35°	42507	40703	34125
40°	18355	20374	17286
45°	12947	16064	13066
50°	4454	11694	4704
55°	2562	4844	2709
60°	1791	2128	1791
65°	1159	1159	1159
70°	716	470	716
75°	0	325	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 22.5°
 Vertical Angle: 45°
 Luminance: 16064 cd/sqm



TEST NUMBER: P793756

CATALOG NUMBER: LER6D55D010-EC6DR3055659035-6LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1912.4	28.3
10°-20°	3079.9	45.5
20°-30°	1330.9	19.7
30°-40°	303.3	4.5
40°-50°	104.2	1.5
50°-60°	25.4	0.4
60°-70°	6.6	0.1
70°-80°	0.7	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6323.2	93.5
0°-40°	6626.6	98.0
0°-60°	6756.1	99.9
0°-90°	6763.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6763.4	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	21748	21748	21748	21748	21748	
5°	21043	21023	21018	21062	21044	1914
15°	11530	11392	11469	11431	11411	3087
25°	2710	2812	3056	2741	2654	1297
35°	455	464	436	432	365	309
45°	120	148	148	148	121	85
55°	19	20	36	21	20	19
65°	6	6	6	6	6	6
75°	0	0	1	0	0	1
85°	0	0	0	0	0	0
90°	0	0	0	0	0	0



TEST NUMBER: P793756

CATALOG NUMBER: LER6D55D010-EC6DR3055659035-6LBS1H

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	21747.8	21747.8	21747.8	21747.8	21747.8
2.5°	21603.6	21588.7	21597.2	21607.9	21612.1
5°	21043.0	21022.8	21018.5	21062.3	21044.1
7.5°	19912.3	19883.5	19839.7	19939.0	20031.9
10°	18018.1	17986.1	17891.1	17938.1	18013.9
12.5°	15221.7	15118.1	15116.0	15265.5	15245.2
15°	11530.5	11391.7	11468.6	11431.2	11411.0
17.5°	7753.9	7700.5	7803.1	7772.1	7638.6
20°	5577.9	5591.8	5787.2	5688.9	5570.4
22.5°	4070.2	4120.4	4352.1	4099.1	4006.2
25°	2709.9	2812.4	3055.9	2740.9	2654.4
27.5°	1666.7	1713.7	1960.4	1645.4	1598.4
30°	1036.8	1013.3	1129.7	969.5	903.3
32.5°	680.2	650.3	687.6	617.2	563.8
35°	454.9	464.5	435.6	432.4	365.2
37.5°	284.0	326.7	288.3	307.5	234.9
40°	183.7	237.0	203.9	225.3	173.0
42.5°	150.6	182.6	167.6	178.3	153.8
45°	119.6	148.4	148.4	148.4	120.7
47.5°	66.2	99.3	127.1	101.4	70.5
50°	37.4	50.2	98.2	52.3	39.5
52.5°	25.6	28.8	67.3	29.9	26.7
55°	19.2	20.3	36.3	21.4	20.3
57.5°	14.9	16.0	19.2	16.0	14.9
60°	11.7	11.7	13.9	12.8	11.7
62.5°	8.5	8.5	9.6	8.5	8.5
65°	6.4	6.4	6.4	6.4	6.4
67.5°	3.2	4.3	4.3	4.3	4.3
70°	3.2	2.1	2.1	2.1	3.2
72.5°	2.1	1.1	1.1	1.1	1.1
75°	0.0	0.0	1.1	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report





— 0°-180° - - 45°-225° - - - - 90°-270°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)