

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P794529

Luminaire Tested: LER6D60D010-EC6DR6055659040-6LBDP1LI

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P794529
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER6D60D010-EC6DR6055659040-6LBDP1LI
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR CLEAR TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7974.8 lumens
Efficiency: N/A
Efficacy: 123.8 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 64.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P794529
CATALOG NUMBER: LER6D60D010-EC6DR6055659040-6LBDP1LI

Luminous Intensity Polar Plot





TEST NUMBER: P794529

CATALOG NUMBER: LER6D60D010-EC6DR6055659040-6LBDP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | 0 |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |
| 1 | 113 | 110 | 108 | 105 | 111 | 108 | 106 | 104 | 104 | 102 | 100 | 100 | 99 | 97 | 97 | 96 | 95 | 93 |
| 2 | 107 | 102 | 98 | 95 | 105 | 101 | 97 | 94 | 97 | 94 | 92 | 94 | 92 | 90 | 92 | 90 | 88 | 86 |
| 3 | 102 | 96 | 90 | 86 | 100 | 94 | 89 | 86 | 91 | 88 | 84 | 89 | 86 | 83 | 87 | 84 | 82 | 80 |
| 4 | 97 | 89 | 84 | 80 | 95 | 88 | 83 | 79 | 86 | 82 | 78 | 84 | 80 | 77 | 82 | 79 | 76 | 75 |
| 5 | 92 | 84 | 78 | 74 | 91 | 83 | 78 | 74 | 81 | 77 | 73 | 80 | 76 | 72 | 78 | 75 | 72 | 70 |
| 6 | 88 | 79 | 73 | 69 | 87 | 78 | 73 | 69 | 77 | 72 | 68 | 75 | 71 | 68 | 74 | 70 | 67 | 66 |
| 7 | 84 | 75 | 69 | 65 | 83 | 74 | 68 | 64 | 73 | 68 | 64 | 72 | 67 | 64 | 71 | 67 | 63 | 62 |
| 8 | 80 | 71 | 65 | 61 | 79 | 70 | 65 | 61 | 69 | 64 | 60 | 68 | 64 | 60 | 67 | 63 | 60 | 59 |
| 9 | 77 | 67 | 61 | 57 | 75 | 67 | 61 | 57 | 66 | 61 | 57 | 65 | 60 | 57 | 64 | 60 | 57 | 55 |
| 10 | 73 | 64 | 58 | 54 | 72 | 63 | 58 | 54 | 62 | 58 | 54 | 62 | 57 | 54 | 61 | 57 | 54 | 53 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|---------|
| | 0° |
| 0° | 1034820 |
| 5° | 1060258 |
| 10° | 1073072 |
| 15° | 1022243 |
| 20° | 901301 |
| 25° | 729002 |
| 30° | 493110 |
| 35° | 247105 |
| 40° | 40079 |
| 45° | 39232 |
| 50° | 40013 |
| 55° | 40613 |
| 60° | 41738 |
| 65° | 42710 |
| 70° | 43702 |
| 75° | 44241 |
| 80° | 42660 |
| 85° | 35478 |

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 75°
 Luminance: 44241 cd/sqm



TEST NUMBER: P794529

CATALOG NUMBER: LER6D60D010-EC6DR6055659040-6LBDP1LI

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 923.9 | 11.6 |
| 10°-20° | 2499.7 | 31.3 |
| 20°-30° | 2689.5 | 33.7 |
| 30°-40° | 1169.1 | 14.7 |
| 40°-50° | 196.3 | 2.5 |
| 50°-60° | 190.9 | 2.4 |
| 60°-70° | 163.3 | 2.0 |
| 70°-80° | 109.3 | 1.4 |
| 80°-90° | 32.7 | 0.4 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 6113.2 | 76.7 |
| 0°-40° | 7282.3 | 91.3 |
| 0°-60° | 7669.5 | 96.2 |
| 0°-90° | 7974.8 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 7974.8 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|------|------|
| 0° | 9471 | |
| 5° | 9667 | 924 |
| 15° | 9037 | 2500 |
| 25° | 6047 | 2690 |
| 35° | 1853 | 1169 |
| 45° | 254 | 196 |
| 55° | 213 | 191 |
| 65° | 165 | 163 |
| 75° | 105 | 109 |
| 85° | 28 | 33 |
| 90° | 0 | |



TEST NUMBER: P794529

CATALOG NUMBER: LER6D60D010-EC6DR6055659040-6LBDP1LI

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|--------|
| 0° | 9471.1 |
| 2.5° | 9737.3 |
| 5° | 9667.0 |
| 7.5° | 9689.2 |
| 10° | 9672.0 |
| 12.5° | 9472.3 |
| 15° | 9037.2 |
| 17.5° | 8453.0 |
| 20° | 7751.6 |
| 22.5° | 7001.0 |
| 25° | 6047.0 |
| 27.5° | 4836.6 |
| 30° | 3908.5 |
| 32.5° | 3012.4 |
| 35° | 1852.6 |
| 37.5° | 792.5 |
| 40° | 281.0 |
| 42.5° | 258.8 |
| 45° | 253.9 |
| 47.5° | 245.3 |
| 50° | 235.4 |
| 52.5° | 224.3 |
| 55° | 213.2 |
| 57.5° | 202.1 |
| 60° | 191.0 |
| 62.5° | 178.7 |
| 65° | 165.2 |
| 67.5° | 151.6 |
| 70° | 136.8 |
| 72.5° | 120.8 |
| 75° | 104.8 |
| 77.5° | 86.3 |
| 80° | 67.8 |
| 82.5° | 48.1 |
| 85° | 28.3 |
| 87.5° | 9.9 |
| 90° | 0.0 |

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)