

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204970

Luminaire Tested: **LSR6B10D010BZ EC6B10209030 6LBSCMMS1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204970
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR6B10D010BZ EC6B10209030 6LBCSMMS1
Description: PORTFOLIO 6IN CYLINDER
SHALLOW DISTRIBUTION WITH CAST MATTE METALLIC SILVER TRIM
WATTAGE D010TR-10.05 W DE010-10.58 W D5LT-10.2 W DMX-10.6 W DL2-11.8 W
DL3-11.1 W DLE-11.39 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 933.7 lumens
Efficiency: N/A
Efficacy: 94.3 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204970

CATALOG NUMBER: LSR6B10D010BZ EC6B10209030 6LBCSMMS1

Luminous Intensity Polar Plot





TEST NUMBER: P204970

CATALOG NUMBER: LSR6B10D010BZ EC6B10209030 6LBCSMMS1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	111	107	103	100	108	105	101	98	100	98	95	97	94	92	93	91	90	88	88	88	88
2	102	95	89	84	100	93	88	83	90	85	81	86	83	79	83	80	78	76	76	76	76
3	94	85	77	72	92	83	76	71	80	74	70	77	73	69	75	71	67	65	65	65	65
4	87	76	68	62	84	74	67	61	72	66	61	70	64	60	68	63	59	57	57	57	57
5	80	68	60	54	78	67	59	54	65	58	53	63	57	53	61	56	52	50	50	50	50
6	74	62	54	48	72	61	53	47	59	52	47	58	51	47	56	51	46	44	44	44	44
7	69	56	48	42	67	56	48	42	54	47	42	53	46	42	51	46	41	40	40	40	40
8	64	52	44	38	63	51	43	38	50	43	38	48	42	38	47	42	37	36	36	36	36
9	60	48	40	35	59	47	40	34	46	39	34	45	39	34	44	38	34	32	32	32	32
10	57	44	36	31	55	43	36	31	43	36	31	42	35	31	41	35	31	29	29	29	29

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204970

CATALOG NUMBER: LSR6B10D010BZ EC6B10209030 6LBCSMMS1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	40.4	4.3
10°-20°	113.4	12.1
20°-30°	165.6	17.7
30°-40°	189.4	20.3
40°-50°	182.0	19.5
50°-60°	140.6	15.1
60°-70°	78.5	8.4
70°-80°	22.8	2.4
80°-90°	1.0	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	319.4	34.2
0°-40°	508.8	54.5
0°-60°	831.5	89.0
0°-90°	933.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	933.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	429	
5°	425	40
15°	402	113
25°	360	166
35°	303	189
45°	237	182
55°	158	141
65°	78	78
75°	20	23
85°	1	1
90°	0	



TEST NUMBER: P204970

CATALOG NUMBER: LSR6B10D010BZ EC6B10209030 6LBCSMMS1

CANDELA DISTRIBUTION (FULL):

0°	
0°	428.8
2.5°	428.8
5°	425.2
7.5°	423.3
10°	417.3
12.5°	410.1
15°	402.2
17.5°	394.4
20°	382.9
22.5°	373.8
25°	359.9
27.5°	346.0
30°	332.2
32.5°	318.3
35°	303.2
37.5°	288.1
40°	270.6
42.5°	254.9
45°	237.3
47.5°	217.4
50°	198.7
52.5°	178.2
55°	157.6
57.5°	136.5
60°	116.6
62.5°	96.6
65°	78.5
67.5°	61.6
70°	45.9
72.5°	32.0
75°	19.9
77.5°	10.3
80°	3.6
82.5°	1.2
85°	0.6
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)