

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203015

Luminaire Tested: **LSR6B10D010BZ EC6B10209730 6LBWB1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203015
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR6B10D010BZ EC6B10209730 6LBWB1
Description: PORTFOLIO 6IN CYLINDER
WIDE DISTRIBUTION WITH SPECULAR BLACK TRIM
WATTAGE D010TR-10.05 W DE010-10.58 W D5LT-10.2 W DMX-10.6 W DL2-11.8 W
DL3-11.1 W DLE-11.39 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 446.2 lumens
Efficiency: N/A
Efficacy: 45.1 lumens/watt
Spacing Criteria (0/90/45): 1.08 / 1.08 / 1.08
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203015

CATALOG NUMBER: LSR6B10D010BZ EC6B10209730 6LBWB1

Luminous Intensity Polar Plot





TEST NUMBER: P203015

CATALOG NUMBER: LSR6B10D010BZ EC6B10209730 6LBWB1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92																			
2	106	101	97	93	104	99	95	92	96	93	90	93	90	88	90	88	86	84																			
3	100	93	87	83	98	92	86	82	89	85	81	86	83	80	84	81	78	77																			
4	94	86	79	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	79	73	68	87	78	72	67	76	71	67	75	70	66	73	69	66	64																			
6	83	73	67	62	82	72	66	61	71	65	61	69	64	61	68	64	60	59																			
7	78	68	61	56	77	67	61	56	66	60	56	65	60	56	63	59	55	54																			
8	74	63	57	52	73	63	56	52	61	56	52	60	55	51	59	55	51	50																			
9	70	59	52	48	69	58	52	48	57	52	48	57	51	47	56	51	47	46																			
10	66	55	49	44	65	55	49	44	54	48	44	53	48	44	52	47	44	42																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203015

CATALOG NUMBER: LSR6B10D010BZ EC6B10209730 6LBWB1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	31.6	7.1
10°-20°	88.4	19.8
20°-30°	123.9	27.8
30°-40°	118.3	26.5
40°-50°	67.4	15.1
50°-60°	16.5	3.7
60°-70°	0.2	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	243.9	54.7
0°-40°	362.2	81.2
0°-60°	446.0	100.0
0°-90°	446.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	446.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	336	
5°	334	32
15°	314	88
25°	271	124
35°	193	118
45°	86	67
55°	16	16
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P203015

CATALOG NUMBER: LSR6B10D010BZ EC6B10209730 6LBWB1

CANDELA DISTRIBUTION (FULL):

	0°
0°	336.3
2.5°	336.3
5°	333.6
7.5°	330.0
10°	327.2
12.5°	321.8
15°	313.6
17.5°	306.3
20°	297.2
22.5°	285.4
25°	270.9
27.5°	254.5
30°	236.3
32.5°	214.5
35°	192.7
37.5°	166.3
40°	138.2
42.5°	111.8
45°	86.4
47.5°	63.6
50°	44.5
52.5°	28.2
55°	16.4
57.5°	7.3
60°	1.8
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)