

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205177

Luminaire Tested: **LSR6B10D010BZ EC6B10209730 6LBWLI1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P205177  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSR6B10D010BZ EC6B10209730 6LBWL11  
Description: PORTFOLIO 6IN CYLINDER  
WIDE DISTRIBUTION WITH SPECULAR CLEAR TRIM  
WATTAGE D010TR-10.05 W DE010-10.58 W D5LT-10.2 W DMX-10.6 W DL2-11.8 W  
DL3-11.1 W DLE-11.39 W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 801.6 lumens  
Efficiency: N/A  
Efficacy: 81.0 lumens/watt  
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.18  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 9.9  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P205177

CATALOG NUMBER: LSR6B10D010BZ EC6B10209730 6LBWL11

### Luminous Intensity Polar Plot





TEST NUMBER: P205177

CATALOG NUMBER: LSR6B10D010BZ EC6B10209730 6LBWLI1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	107	104	110	107	105	103	103	101	99	100	98	97	96	95	94	92																			
2	106	101	96	92	104	99	95	91	95	92	89	92	90	87	90	87	85	83																			
3	100	92	87	82	97	91	86	81	88	84	80	86	82	79	83	80	77	76																			
4	93	85	78	74	92	84	78	73	81	76	72	79	75	71	77	74	70	69																			
5	88	78	71	66	86	77	71	66	75	70	65	73	69	65	72	68	64	63																			
6	82	72	65	60	81	71	65	60	70	64	59	68	63	59	67	62	59	57																			
7	77	67	60	55	76	66	59	55	65	59	54	63	58	54	62	57	54	52																			
8	73	62	55	50	71	61	55	50	60	54	50	59	54	50	58	53	49	48																			
9	69	57	51	46	67	57	50	46	56	50	46	55	50	46	54	49	46	44																			
10	65	54	47	43	64	53	47	43	52	46	42	51	46	42	51	46	42	41																			

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P205177

CATALOG NUMBER: LSR6B10D010BZ EC6B10209730 6LBWLI1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	48.3	6.0
10°-20°	145.2	18.1
20°-30°	218.9	27.3
30°-40°	224.0	27.9
40°-50°	130.5	16.3
50°-60°	30.0	3.7
60°-70°	3.7	0.5
70°-80°	0.9	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	412.4	51.4
0°-40°	636.4	79.4
0°-60°	797.0	99.4
0°-90°	801.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	801.6	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	501	
5°	504	48
15°	514	145
25°	480	219
35°	364	224
45°	168	131
55°	29	30
65°	3	4
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P205177

CATALOG NUMBER: LSR6B10D010BZ EC6B10209730 6LBWLI1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	500.8
2.5°	499.9
5°	503.5
7.5°	507.1
10°	511.7
12.5°	512.6
15°	514.4
17.5°	512.6
20°	508.0
22.5°	493.5
25°	479.9
27.5°	458.1
30°	429.9
32.5°	400.8
35°	363.5
37.5°	321.7
40°	275.4
42.5°	223.6
45°	168.1
47.5°	117.2
50°	77.3
52.5°	49.1
55°	29.1
57.5°	15.5
60°	8.2
62.5°	4.5
65°	2.7
67.5°	2.7
70°	1.8
72.5°	0.9
75°	0.9
77.5°	0.9
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)