

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203526

Luminaire Tested: **LSR6B10D010BZ EC6B10209035 6LBMMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203526
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR6B10D010BZ EC6B10209035 6LBMMW1
Description: PORTFOLIO 6IN CYLINDER
MEDIUM DISTRIBUTION WITH MATTE WHITE TRIM
WATTAGE D010TR-10.05 W DE010-10.58 W D5LT-10.2 W DMX-10.6 W DL2-11.8 W
DL3-11.1 W DLE-11.39 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 738.9 lumens
Efficiency: N/A
Efficacy: 74.6 lumens/watt
Spacing Criteria (0/90/45): 1 / 1 / 0.97
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203526

CATALOG NUMBER: LSR6B10D010BZ EC6B10209035 6LBMMW1

Luminous Intensity Polar Plot





TEST NUMBER: P203526

CATALOG NUMBER: LSR6B10D010BZ EC6B10209035 6LBMMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	108	104	101	109	105	103	100	101	99	97	98	96	94	94	92	91	89
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79
3	97	88	82	77	95	87	81	76	84	79	75	82	77	74	79	76	73	71
4	90	81	74	68	88	80	73	68	77	72	67	75	70	66	73	69	65	64
5	85	74	67	61	83	73	66	61	71	65	61	69	64	60	68	63	59	58
6	79	68	61	56	78	68	61	56	66	60	55	64	59	55	63	58	54	53
7	75	63	56	51	73	63	56	51	61	55	50	60	54	50	59	54	50	48
8	70	59	52	47	69	58	51	47	57	51	46	56	50	46	55	50	46	44
9	66	55	48	43	65	54	48	43	53	47	43	52	47	43	51	46	43	41
10	63	51	45	40	62	51	44	40	50	44	40	49	44	40	48	43	40	38

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203526

CATALOG NUMBER: LSR6B10D010BZ EC6B10209035 6LBMMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	50.9	6.9
10°-20°	136.4	18.5
20°-30°	183.2	24.8
30°-40°	150.3	20.3
40°-50°	90.2	12.2
50°-60°	60.0	8.1
60°-70°	40.2	5.4
70°-80°	21.6	2.9
80°-90°	6.1	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	370.5	50.1
0°-40°	520.8	70.5
0°-60°	671.0	90.8
0°-90°	738.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	738.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	551	
5°	542	51
15°	486	136
25°	404	183
35°	238	150
45°	114	90
55°	66	60
65°	41	40
75°	20	22
85°	5	6
90°	0	



TEST NUMBER: P203526

CATALOG NUMBER: LSR6B10D010BZ EC6B10209035 6LBMMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	551.4
2.5°	547.3
5°	542.2
7.5°	531.0
10°	517.7
12.5°	501.4
15°	486.1
17.5°	467.8
20°	449.4
22.5°	429.1
25°	403.6
27.5°	373.0
30°	332.2
32.5°	286.4
35°	238.5
37.5°	197.7
40°	163.1
42.5°	135.5
45°	114.1
47.5°	96.8
50°	84.6
52.5°	74.4
55°	66.2
57.5°	59.1
60°	53.0
62.5°	45.9
65°	40.8
67.5°	34.7
70°	29.6
72.5°	24.5
75°	20.4
77.5°	16.3
80°	12.2
82.5°	9.2
85°	5.1
87.5°	2.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)