

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204351

Luminaire Tested: **LSR6B10D010BZ EC6B10209040 6LBSGPH1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P204351  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSR6B10D010BZ EC6B10209040 6LBSGPH1  
Description: PORTFOLIO 6IN CYLINDER  
SHALLOW DISTRIBUTION WITH GRAPHITE HAZE TRIM  
WATTAGE D010TR-10.05 W DE010-10.58 W D5LT-10.2 W DMX-10.6 W DL2-11.8 W  
DL3-11.1 W DLE-11.39 W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 881.1 lumens  
Efficiency: N/A  
Efficacy: 89.0 lumens/watt  
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.26  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 9.9  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P204351

CATALOG NUMBER: LSR6B10D010BZ EC6B10209040 6LBSGPH1

### Luminous Intensity Polar Plot





TEST NUMBER: P204351

CATALOG NUMBER: LSR6B10D010BZ EC6B10209040 6LBSGPH1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |   |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|---|--|--|--|--|--|--|----|--|--|--|--|--|--|--|--|---|
| RF  | 20  |     |     |     |     |     |     |     |     | 20  |     |     |     |     |     |     |     |     | 20 |    |   |  |  |  |  |  |  | 20 |  |  |  |  |  |  |  |  |   |
| RC  | 80  |     |     |     |     |     |     |     |     | 50  |     |     |     |     |     |     |     |     | 30 |    |   |  |  |  |  |  |  | 10 |  |  |  |  |  |  |  |  | 0 |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30 | 10 | 0 |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |
| RCR |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |   |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |    |    |   |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |
| 1   | 111 | 107 | 103 | 100 | 108 | 105 | 102 | 99  | 101 | 98  | 96  | 97  | 95  | 93  | 93  | 92  | 90  | 88  |    |    |   |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |
| 2   | 102 | 95  | 89  | 84  | 100 | 93  | 88  | 83  | 90  | 85  | 82  | 87  | 83  | 80  | 84  | 81  | 78  | 76  |    |    |   |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |
| 3   | 94  | 85  | 78  | 72  | 92  | 83  | 77  | 71  | 80  | 75  | 70  | 78  | 73  | 69  | 75  | 71  | 68  | 66  |    |    |   |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |
| 4   | 87  | 76  | 68  | 62  | 85  | 75  | 67  | 62  | 72  | 66  | 61  | 70  | 65  | 60  | 68  | 63  | 59  | 57  |    |    |   |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |
| 5   | 80  | 68  | 60  | 54  | 78  | 67  | 60  | 54  | 65  | 59  | 53  | 63  | 58  | 53  | 62  | 56  | 52  | 50  |    |    |   |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |
| 6   | 74  | 62  | 54  | 48  | 73  | 61  | 53  | 48  | 59  | 52  | 47  | 58  | 52  | 47  | 56  | 51  | 47  | 45  |    |    |   |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |
| 7   | 69  | 57  | 48  | 43  | 68  | 56  | 48  | 43  | 54  | 47  | 42  | 53  | 47  | 42  | 52  | 46  | 42  | 40  |    |    |   |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |
| 8   | 65  | 52  | 44  | 38  | 63  | 51  | 44  | 38  | 50  | 43  | 38  | 49  | 42  | 38  | 48  | 42  | 38  | 36  |    |    |   |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |
| 9   | 60  | 48  | 40  | 35  | 59  | 47  | 40  | 35  | 46  | 39  | 35  | 45  | 39  | 34  | 44  | 38  | 34  | 32  |    |    |   |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |
| 10  | 57  | 44  | 37  | 32  | 56  | 44  | 36  | 32  | 43  | 36  | 32  | 42  | 36  | 31  | 41  | 35  | 31  | 30  |    |    |   |  |  |  |  |  |  |    |  |  |  |  |  |  |  |  |   |

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P204351

CATALOG NUMBER: LSR6B10D010BZ EC6B10209040 6LBSGPH1

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 38.5   | 4.4       |
| 10°-20°   | 108.2  | 12.3      |
| 20°-30°   | 157.8  | 17.9      |
| 30°-40°   | 179.9  | 20.4      |
| 40°-50°   | 172.6  | 19.6      |
| 50°-60°   | 132.1  | 15.0      |
| 60°-70°   | 72.5   | 8.2       |
| 70°-80°   | 19.3   | 2.2       |
| 80°-90°   | 0.3    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 304.4  | 34.6      |
| 0°-40°    | 484.3  | 55.0      |
| 0°-60°    | 789.0  | 89.6      |
| 0°-90°    | 881.1  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 881.1  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 409 |      |
| 5°  | 406 | 39   |
| 15° | 384 | 108  |
| 25° | 343 | 158  |
| 35° | 288 | 180  |
| 45° | 224 | 173  |
| 55° | 148 | 132  |
| 65° | 73  | 73   |
| 75° | 17  | 19   |
| 85° | 0   | 0    |
| 90° | 0   |      |



TEST NUMBER: P204351

CATALOG NUMBER: LSR6B10D010BZ EC6B10209040 6LBSGPH1

**CANDELA DISTRIBUTION (FULL):**

|       | 0°    |
|-------|-------|
| 0°    | 409.2 |
| 2.5°  | 408.2 |
| 5°    | 406.1 |
| 7.5°  | 402.9 |
| 10°   | 398.7 |
| 12.5° | 391.3 |
| 15°   | 383.9 |
| 17.5° | 375.4 |
| 20°   | 365.9 |
| 22.5° | 354.3 |
| 25°   | 342.6 |
| 27.5° | 331.0 |
| 30°   | 316.2 |
| 32.5° | 302.4 |
| 35°   | 287.6 |
| 37.5° | 272.8 |
| 40°   | 258.0 |
| 42.5° | 242.2 |
| 45°   | 224.2 |
| 47.5° | 206.2 |
| 50°   | 187.2 |
| 52.5° | 167.1 |
| 55°   | 148.0 |
| 57.5° | 129.0 |
| 60°   | 108.9 |
| 62.5° | 89.9  |
| 65°   | 73.0  |
| 67.5° | 56.0  |
| 70°   | 41.2  |
| 72.5° | 27.5  |
| 75°   | 16.9  |
| 77.5° | 7.4   |
| 80°   | 2.1   |
| 82.5° | 0.0   |
| 85°   | 0.0   |
| 87.5° | 0.0   |
| 90°   | 0.0   |



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)