

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204982

Luminaire Tested: **LSR6B15D010BZ EC6B10209030 6LBSCMMS1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P204982  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSR6B15D010BZ EC6B10209030 6LBCSMMS1  
Description: PORTFOLIO 6IN CYLINDER  
SHALLOW DISTRIBUTION WITH CAST MATTE METALLIC SILVER TRIM  
WATTAGE D010TR-14.39 W DE010-14.29 W D5LT-14.34 W DMX-14.46 W DL2-15.8 W  
DL3-15.28 W DLE-15.432 W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1288.2 lumens  
Efficiency: N/A  
Efficacy: 90.1 lumens/watt  
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 14.3  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P204982

CATALOG NUMBER: LSR6B15D010BZ EC6B10209030 6LBCSMMS1

### Luminous Intensity Polar Plot





TEST NUMBER: P204982

CATALOG NUMBER: LSR6B15D010BZ EC6B10209030 6LBCSMMS1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	107	103	100	108	105	101	98	100	98	95	97	94	92	93	91	90	88
2	102	95	89	84	99	93	88	83	90	85	81	86	83	79	83	80	78	76
3	94	85	77	72	92	83	76	71	80	74	70	77	73	69	75	71	67	65
4	87	76	68	62	84	74	67	61	72	66	61	70	64	60	68	63	59	57
5	80	68	60	54	78	67	59	54	65	58	53	63	57	53	61	56	52	50
6	74	62	54	48	72	61	53	47	59	52	47	58	51	47	56	51	46	44
7	69	56	48	42	67	56	48	42	54	47	42	53	46	42	51	46	41	40
8	64	52	44	38	63	51	43	38	50	43	38	48	42	38	47	42	37	36
9	60	48	40	35	59	47	40	34	46	39	34	45	39	34	44	38	34	32
10	57	44	36	31	55	43	36	31	43	36	31	42	35	31	41	35	31	29

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P204982

CATALOG NUMBER: LSR6B15D010BZ EC6B10209030 6LBCSMMS1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	55.8	4.3
10°-20°	156.4	12.1
20°-30°	228.5	17.7
30°-40°	261.3	20.3
40°-50°	251.2	19.5
50°-60°	193.9	15.1
60°-70°	108.2	8.4
70°-80°	31.5	2.4
80°-90°	1.4	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	440.7	34.2
0°-40°	702.0	54.5
0°-60°	1147.1	89.0
0°-90°	1288.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1288.2	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	592	
5°	587	56
15°	555	156
25°	497	228
35°	418	261
45°	327	251
55°	218	194
65°	108	108
75°	28	32
85°	1	1
90°	0	



TEST NUMBER: P204982

CATALOG NUMBER: LSR6B15D010BZ EC6B10209030 6LBCSMMS1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	591.6
2.5°	591.6
5°	586.6
7.5°	584.1
10°	575.7
12.5°	565.7
15°	554.9
17.5°	544.1
20°	528.2
22.5°	515.7
25°	496.6
27.5°	477.4
30°	458.3
32.5°	439.1
35°	418.3
37.5°	397.4
40°	373.3
42.5°	351.6
45°	327.4
47.5°	300.0
50°	274.1
52.5°	245.8
55°	217.5
57.5°	188.3
60°	160.8
62.5°	133.3
65°	108.3
67.5°	85.0
70°	63.3
72.5°	44.2
75°	27.5
77.5°	14.2
80°	5.0
82.5°	1.7
85°	0.8
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)