

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204357

Luminaire Tested: **LSR6B15D010BZ EC6B10208035 6LBSGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204357
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR6B15D010BZ EC6B10208035 6LBSGPH1
Description: PORTFOLIO 6IN CYLINDER
SHALLOW DISTRIBUTION WITH GRAPHITE HAZE TRIM
WATTAGE D010TR-14.39 W DE010-14.29 W D5LT-14.34 W DMX-14.46 W DL2-15.8 W
DL3-15.28 W DLE-15.432 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1436.0 lumens
Efficiency: N/A
Efficacy: 100.4 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.26
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204357

CATALOG NUMBER: LSR6B15D010BZ EC6B10208035 6LBSGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P204357

CATALOG NUMBER: LSR6B15D010BZ EC6B10208035 6LBSGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	103	100	108	105	102	99	101	98	96	97	95	93	93	91	90	88			
2	102	95	89	84	100	93	88	83	90	85	82	87	83	80	84	81	78	76			
3	94	85	78	72	92	83	77	71	80	75	70	78	73	69	75	71	68	66			
4	87	76	68	62	85	75	67	62	72	66	61	70	65	60	68	63	59	57			
5	80	68	60	54	78	67	60	54	65	59	53	63	58	53	62	56	52	50			
6	74	62	54	48	73	61	53	48	59	52	47	58	52	47	56	51	47	45			
7	69	57	48	43	68	56	48	43	54	47	42	53	47	42	52	46	42	40			
8	65	52	44	38	63	51	44	38	50	43	38	49	42	38	48	42	38	36			
9	60	48	40	35	59	47	40	35	46	39	35	45	39	34	44	38	34	32			
10	57	44	37	32	56	44	36	32	43	36	31	42	36	31	41	35	31	30			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204357

CATALOG NUMBER: LSR6B15D010BZ EC6B10208035 6LBSGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	62.8	4.4
10°-20°	176.3	12.3
20°-30°	257.1	17.9
30°-40°	293.2	20.4
40°-50°	281.2	19.6
50°-60°	215.4	15.0
60°-70°	118.2	8.2
70°-80°	31.4	2.2
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	496.1	34.6
0°-40°	789.3	55.0
0°-60°	1285.9	89.5
0°-90°	1436.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1436.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	667	
5°	662	63
15°	626	176
25°	558	257
35°	469	293
45°	365	281
55°	241	215
65°	119	118
75°	28	31
85°	0	0
90°	0	



TEST NUMBER: P204357

CATALOG NUMBER: LSR6B15D010BZ EC6B10208035 6LBSGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	666.9
2.5°	665.2
5°	661.8
7.5°	656.6
10°	649.7
12.5°	637.6
15°	625.6
17.5°	611.8
20°	596.3
22.5°	577.3
25°	558.4
27.5°	539.4
30°	515.3
32.5°	492.9
35°	468.8
37.5°	444.6
40°	420.5
42.5°	394.6
45°	365.4
47.5°	336.1
50°	305.0
52.5°	272.3
55°	241.3
57.5°	210.2
60°	177.5
62.5°	146.5
65°	118.9
67.5°	91.3
70°	67.2
72.5°	44.8
75°	27.6
77.5°	12.1
80°	3.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)