

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204985

Luminaire Tested: **LSR6B15D010BZ EC6B10209050 6LBSCMMS1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P204985  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSR6B15D010BZ EC6B10209050 6LBCSMMS1  
Description: PORTFOLIO 6IN CYLINDER  
SHALLOW DISTRIBUTION WITH CAST MATTE METALLIC SILVER TRIM  
WATTAGE D010TR-14.39 W DE010-14.29 W D5LT-14.34 W DMX-14.46 W DL2-15.8 W  
DL3-15.28 W DLE-15.432 W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1313.7 lumens  
Efficiency: N/A  
Efficacy: 91.9 lumens/watt  
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 14.3  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P204985

CATALOG NUMBER: LSR6B15D010BZ EC6B10209050 6LBCSMMS1

### Luminous Intensity Polar Plot





TEST NUMBER: P204985

CATALOG NUMBER: LSR6B15D010BZ EC6B10209050 6LBCSMMS1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	103	100	108	105	101	98	100	98	95	97	94	92	93	91	90	88			
2	102	95	89	84	100	93	88	83	90	85	81	86	83	79	83	80	78	76			
3	94	85	77	72	92	83	76	71	80	74	70	77	73	69	75	71	67	65			
4	87	76	68	62	84	74	67	61	72	66	61	70	64	60	68	63	59	57			
5	80	68	60	54	78	67	59	54	65	58	53	63	57	53	61	56	52	50			
6	74	62	54	48	72	61	53	47	59	52	47	58	51	47	56	51	46	44			
7	69	56	48	42	67	56	48	42	54	47	42	53	46	42	51	46	41	40			
8	64	52	44	38	63	51	43	38	50	43	38	48	42	38	47	42	37	36			
9	60	48	40	35	59	47	40	34	46	39	34	45	39	34	44	38	34	32			
10	57	44	36	31	55	43	36	31	43	36	31	42	35	31	41	35	31	29			

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P204985

CATALOG NUMBER: LSR6B15D010BZ EC6B10209050 6LBCSMMS1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	56.9	4.3
10°-20°	159.5	12.1
20°-30°	233.0	17.7
30°-40°	266.5	20.3
40°-50°	256.1	19.5
50°-60°	197.8	15.1
60°-70°	110.4	8.4
70°-80°	32.1	2.4
80°-90°	1.4	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	449.4	34.2
0°-40°	715.9	54.5
0°-60°	1169.8	89.0
0°-90°	1313.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1313.7	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	603	
5°	598	57
15°	566	160
25°	506	233
35°	426	266
45°	334	256
55°	222	198
65°	110	110
75°	28	32
85°	1	1
90°	0	



TEST NUMBER: P204985

CATALOG NUMBER: LSR6B15D010BZ EC6B10209050 6LBCSMMS1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	603.3
2.5°	603.3
5°	598.2
7.5°	595.6
10°	587.1
12.5°	576.9
15°	565.9
17.5°	554.8
20°	538.7
22.5°	526.0
25°	506.4
27.5°	486.9
30°	467.3
32.5°	447.8
35°	426.5
37.5°	405.3
40°	380.7
42.5°	358.6
45°	333.9
47.5°	305.9
50°	279.5
52.5°	250.7
55°	221.8
57.5°	192.0
60°	164.0
62.5°	136.0
65°	110.5
67.5°	86.7
70°	64.6
72.5°	45.0
75°	28.0
77.5°	14.4
80°	5.1
82.5°	1.7
85°	0.8
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)