

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204993

Luminaire Tested: **LSR6B20D010BZ EC6B10209024 6LBCSMMS1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P204993  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSR6B20D010BZ EC6B10209024 6LBCSMMS1  
Description: PORTFOLIO 6IN CYLINDER  
SHALLOW DISTRIBUTION WITH CAST MATTE METALLIC SILVER TRIM  
WATTAGE D010TR-21.86 W DE010-20.46 W D5LT-21.24 W DMX-20.89 W DL2-22.5 W  
DL3-21.8 6 W DLE-22.46 W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1514.4 lumens  
Efficiency: N/A  
Efficacy: 72.8 lumens/watt  
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 20.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P204993

CATALOG NUMBER: LSR6B20D010BZ EC6B10209024 6LBCSMMS1

### Luminous Intensity Polar Plot





TEST NUMBER: P204993

CATALOG NUMBER: LSR6B20D010BZ EC6B10209024 6LBCSMMS1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	111	107	103	100	108	105	101	98	100	98	95	97	94	92	93	91	90	88																			
2	102	95	89	84	99	93	88	83	90	85	81	86	83	79	83	80	78	76																			
3	94	85	77	72	92	83	76	71	80	74	70	77	73	69	75	71	67	65																			
4	87	76	68	62	84	74	67	61	72	66	61	70	64	60	68	63	59	57																			
5	80	68	60	54	78	67	59	54	65	58	53	63	57	53	61	56	52	50																			
6	74	62	54	48	72	61	53	47	59	52	47	58	51	47	56	51	46	44																			
7	69	56	48	42	67	56	48	42	54	47	42	53	46	42	51	46	41	40																			
8	64	52	44	38	63	51	43	38	50	43	38	48	42	38	47	42	37	36																			
9	60	48	40	35	59	47	40	34	46	39	34	45	39	34	44	38	34	32																			
10	57	44	36	31	55	43	36	31	43	36	31	42	35	31	41	35	31	29																			

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P204993

CATALOG NUMBER: LSR6B20D010BZ EC6B10209024 6LBCSMMS1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	65.5	4.3
10°-20°	183.9	12.1
20°-30°	268.6	17.7
30°-40°	307.2	20.3
40°-50°	295.3	19.5
50°-60°	228.0	15.1
60°-70°	127.2	8.4
70°-80°	37.0	2.4
80°-90°	1.6	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	518.1	34.2
0°-40°	825.3	54.5
0°-60°	1348.6	89.0
0°-90°	1514.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1514.4	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	696	
5°	690	66
15°	652	184
25°	584	269
35°	492	307
45°	385	295
55°	256	228
65°	127	127
75°	32	37
85°	1	2
90°	0	



TEST NUMBER: P204993

CATALOG NUMBER: LSR6B20D010BZ EC6B10209024 6LBCSMMS1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	695.5
2.5°	695.5
5°	689.6
7.5°	686.6
10°	676.9
12.5°	665.1
15°	652.4
17.5°	639.6
20°	621.0
22.5°	606.3
25°	583.8
27.5°	561.3
30°	538.7
32.5°	516.2
35°	491.7
37.5°	467.2
40°	438.8
42.5°	413.4
45°	385.0
47.5°	352.6
50°	322.3
52.5°	289.0
55°	255.7
57.5°	221.4
60°	189.0
62.5°	156.7
65°	127.3
67.5°	99.9
70°	74.4
72.5°	51.9
75°	32.3
77.5°	16.7
80°	5.9
82.5°	2.0
85°	1.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)