

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203349

Luminaire Tested: **LSR6B20D010BZ EC6B10209727 6LBMWH1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P203349  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSR6B20D010BZ EC6B10209727 6LBMWH1  
Description: PORTFOLIO 6IN CYLINDER  
MEDIUM DISTRIBUTION WITH WHEAT TRIM  
WATTAGE D010TR-21.86 W DE010-20.46 W D5LT-21.24 W DMX-20.89 W DL2-22.5 W  
DL3-21.8 6 W DLE-22.46 W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1149.1 lumens  
Efficiency: N/A  
Efficacy: 55.2 lumens/watt  
Spacing Criteria (0/90/45): 0.83 / 0.83 / 0.85  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 20.8  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P203349

CATALOG NUMBER: LSR6B20D010BZ EC6B10209727 6LBMWH1

### Luminous Intensity Polar Plot





TEST NUMBER: P203349

CATALOG NUMBER: LSR6B20D010BZ EC6B10209727 6LBMWH1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									20									
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																			
RCR																																														
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																												
1	114	111	108	106	111	109	106	104	105	103	101	101	100	98	97	96	95	94																												
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	92	91	89	87																												
3	103	96	91	87	101	95	90	87	92	88	85	90	87	84	88	85	83	81																												
4	97	90	85	80	96	89	84	80	87	82	79	85	81	78	83	80	77	76																												
5	93	84	79	74	91	83	78	74	82	77	73	80	76	73	78	75	72	71																												
6	88	79	73	69	87	78	73	69	77	72	68	76	71	68	74	70	67	66																												
7	84	75	69	64	82	74	68	64	73	68	64	71	67	64	70	66	63	62																												
8	80	70	64	60	78	70	64	60	69	64	60	68	63	60	67	62	59	58																												
9	76	66	61	57	75	66	60	57	65	60	56	64	59	56	63	59	56	55																												
10	72	63	57	53	71	62	57	53	62	57	53	61	56	53	60	56	53	52																												

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P203349

CATALOG NUMBER: LSR6B20D010BZ EC6B10209727 6LBMWH1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	131.0	11.4
10°-20°	321.7	28.0
20°-30°	372.2	32.4
30°-40°	237.9	20.7
40°-50°	67.5	5.9
50°-60°	12.1	1.0
60°-70°	4.9	0.4
70°-80°	1.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	825.0	71.8
0°-40°	1062.9	92.5
0°-60°	1142.5	99.4
0°-90°	1149.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1149.1	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1434	
5°	1408	131
15°	1154	322
25°	821	372
35°	376	238
45°	78	67
55°	11	12
65°	5	5
75°	2	2
85°	0	0
90°	0	



TEST NUMBER: P203349

CATALOG NUMBER: LSR6B20D010BZ EC6B10209727 6LBMWH1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1433.5
2.5°	1431.9
5°	1407.9
7.5°	1364.8
10°	1304.0
12.5°	1233.7
15°	1153.8
17.5°	1070.7
20°	989.2
22.5°	909.3
25°	821.4
27.5°	725.5
30°	618.5
32.5°	498.6
35°	375.5
37.5°	271.7
40°	188.6
42.5°	124.7
45°	78.3
47.5°	46.3
50°	27.2
52.5°	16.0
55°	11.2
57.5°	9.6
60°	8.0
62.5°	6.4
65°	4.8
67.5°	3.2
70°	3.2
72.5°	1.6
75°	1.6
77.5°	1.6
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)