

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P202722

Luminaire Tested: **LSR6B20D010BZ EC6B10208035 6LBWH1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P202722  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSR6B20D010BZ EC6B10208035 6LBWH1  
Description: PORTFOLIO 6IN CYLINDER  
WIDE DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM  
WATTAGE D010TR-21.86 W DE010-20.46 W D5LT-21.24 W DMX-20.89 W DL2-22.5 W  
DL3-21.8 6 W DLE-22.46 W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1847.3 lumens  
Efficiency: N/A  
Efficacy: 88.8 lumens/watt  
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.16  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 20.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P202722

CATALOG NUMBER: LSR6B20D010BZ EC6B10208035 6LBWH1

### Luminous Intensity Polar Plot





TEST NUMBER: P202722

CATALOG NUMBER: LSR6B20D010BZ EC6B10208035 6LBWH1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20																	
RC	80									50									30									10									0								
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0															
RCR																																													
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																											
1	112	109	106	103	110	107	104	101	103	100	98	99	97	95	95	94	93	91																											
2	105	99	94	90	103	97	93	89	94	90	87	91	88	85	88	85	83	81																											
3	98	90	84	79	96	89	83	78	86	81	77	83	79	76	81	78	75	73																											
4	92	82	75	70	90	81	75	70	79	73	69	77	72	68	75	71	67	65																											
5	86	75	68	63	84	74	68	63	72	66	62	71	65	61	69	64	61	59																											
6	80	69	62	57	78	68	61	56	67	61	56	65	60	56	64	59	55	53																											
7	75	64	56	51	73	63	56	51	62	55	51	60	55	51	59	54	50	49																											
8	70	59	52	47	69	58	51	47	57	51	46	56	50	46	55	50	46	44																											
9	66	55	48	43	65	54	47	43	53	47	43	52	47	42	51	46	42	41																											
10	62	51	44	40	61	50	44	39	50	43	39	49	43	39	48	43	39	38																											

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P202722

CATALOG NUMBER: LSR6B20D010BZ EC6B10208035 6LBWH1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	107.6	5.8
10°-20°	305.4	16.5
20°-30°	447.7	24.2
30°-40°	466.0	25.2
40°-50°	322.4	17.5
50°-60°	140.4	7.6
60°-70°	43.0	2.3
70°-80°	12.9	0.7
80°-90°	2.0	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	860.7	46.6
0°-40°	1326.6	71.8
0°-60°	1789.4	96.9
0°-90°	1847.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1847.3	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1139	
5°	1135	108
15°	1084	305
25°	979	448
35°	754	466
45°	416	322
55°	151	140
65°	41	43
75°	12	13
85°	2	2
90°	0	



TEST NUMBER: P202722

CATALOG NUMBER: LSR6B20D010BZ EC6B10208035 6LBWH1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1139.4
2.5°	1141.8
5°	1134.6
7.5°	1125.0
10°	1113.0
12.5°	1101.1
15°	1084.3
17.5°	1062.8
20°	1038.8
22.5°	1012.5
25°	979.0
27.5°	935.9
30°	880.9
32.5°	823.4
35°	754.0
37.5°	677.4
40°	588.8
42.5°	500.3
45°	416.5
47.5°	337.5
50°	268.1
52.5°	203.5
55°	150.8
57.5°	107.7
60°	74.2
62.5°	55.1
65°	40.7
67.5°	31.1
70°	21.5
72.5°	16.8
75°	12.0
77.5°	7.2
80°	4.8
82.5°	2.4
85°	2.4
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)