

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204489

Luminaire Tested: **LSR6B30D010BZ EC6B30509024 6LBSB1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204489
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR6B30D010BZ EC6B30509024 6LBSB1
Description: PORTFOLIO 6IN CYLINDER
SHALLOW DISTRIBUTION WITH SPECULAR BLACK TRIM
WATTAGE D010TR-27.4 W DE010-27.95 W D5LT-27.65 W DMX-27.73 W DL2-29.56 W
DL3-29.67 W DLE-29.73 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1954.7 lumens
Efficiency: N/A
Efficacy: 69.8 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.3
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204489

CATALOG NUMBER: LSR6B30D010BZ EC6B30509024 6LBSB1

Luminous Intensity Polar Plot





TEST NUMBER: P204489

CATALOG NUMBER: LSR6B30D010BZ EC6B30509024 6LBSB1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	111	107	103	100	108	105	101	98	100	98	95	97	94	93	93	91	90	88																			
2	102	95	89	84	100	93	88	83	90	85	81	86	83	79	84	80	78	76																			
3	94	84	77	72	91	83	76	71	80	74	70	77	73	68	75	71	67	65																			
4	86	76	68	62	84	74	67	61	72	65	60	70	64	60	68	63	59	57																			
5	80	68	60	54	78	67	59	53	65	58	53	63	57	52	61	56	52	50																			
6	74	62	53	47	72	61	53	47	59	52	47	57	51	46	56	50	46	44																			
7	69	56	48	42	67	55	48	42	54	47	42	52	46	41	51	45	41	39																			
8	64	51	43	38	63	51	43	38	49	42	37	48	42	37	47	41	37	35																			
9	60	47	39	34	59	47	39	34	46	39	34	45	38	34	44	38	34	32																			
10	56	44	36	31	55	43	36	31	42	36	31	41	35	31	40	35	31	29																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204489

CATALOG NUMBER: LSR6B30D010BZ EC6B30509024 6LBSB1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	81.4	4.2
10°-20°	230.9	11.8
20°-30°	343.5	17.6
30°-40°	399.7	20.4
40°-50°	389.6	19.9
50°-60°	299.7	15.3
60°-70°	165.7	8.5
70°-80°	43.9	2.2
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	655.8	33.6
0°-40°	1055.6	54.0
0°-60°	1744.8	89.3
0°-90°	1954.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1954.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	862	
5°	857	81
15°	818	231
25°	746	344
35°	642	400
45°	506	390
55°	334	300
65°	166	166
75°	37	44
85°	0	0
90°	0	



TEST NUMBER: P204489

CATALOG NUMBER: LSR6B30D010BZ EC6B30509024 6LBSB1

CANDELA DISTRIBUTION (FULL):

	0°
0°	862.3
2.5°	862.3
5°	857.3
7.5°	849.9
10°	844.9
12.5°	830.1
15°	817.7
17.5°	805.3
20°	788.0
22.5°	770.6
25°	745.8
27.5°	721.1
30°	696.3
32.5°	669.0
35°	641.8
37.5°	607.1
40°	577.3
42.5°	545.1
45°	505.5
47.5°	468.3
50°	426.2
52.5°	381.6
55°	334.5
57.5°	289.9
60°	247.8
62.5°	205.7
65°	166.0
67.5°	128.8
70°	94.2
72.5°	64.4
75°	37.2
77.5°	17.3
80°	2.5
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)