

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204182

Luminaire Tested: **LSR6B30D010BZ EC6B30509030 6LBSH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204182
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR6B30D010BZ EC6B30509030 6LBSH1
Description: PORTFOLIO 6IN CYLINDER
SHALLOW DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
WATTAGE D010TR-27.4 W DE010-27.95 W D5LT-27.65 W DMX-27.73 W DL2-29.56 W
DL3-29.67 W DLE-29.73 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2628.2 lumens
Efficiency: N/A
Efficacy: 93.9 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204182

CATALOG NUMBER: LSR6B30D010BZ EC6B30509030 6LBSH1

Luminous Intensity Polar Plot





TEST NUMBER: P204182

CATALOG NUMBER: LSR6B30D010BZ EC6B30509030 6LBSH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77			
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67			
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51			
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46			
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41			
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37			
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34			
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204182

CATALOG NUMBER: LSR6B30D010BZ EC6B30509030 6LBSH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	128.8	4.9
10°-20°	349.9	13.3
20°-30°	486.0	18.5
30°-40°	530.3	20.2
40°-50°	494.7	18.8
50°-60°	375.5	14.3
60°-70°	205.6	7.8
70°-80°	56.6	2.2
80°-90°	0.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	964.7	36.7
0°-40°	1495.0	56.9
0°-60°	2365.2	90.0
0°-90°	2628.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2628.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1375	
5°	1363	129
15°	1247	350
25°	1056	486
35°	848	530
45°	642	495
55°	420	376
65°	206	206
75°	49	57
85°	0	1
90°	0	



TEST NUMBER: P204182

CATALOG NUMBER: LSR6B30D010BZ EC6B30509030 6LBSH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	1374.6
2.5°	1374.6
5°	1363.0
7.5°	1345.6
10°	1319.6
12.5°	1284.9
15°	1247.2
17.5°	1200.9
20°	1157.5
22.5°	1105.4
25°	1056.2
27.5°	1007.0
30°	952.1
32.5°	900.0
35°	847.9
37.5°	795.8
40°	746.6
42.5°	694.5
45°	642.4
47.5°	590.3
50°	532.5
52.5°	477.5
55°	419.6
57.5°	364.6
60°	309.6
62.5°	254.7
65°	205.5
67.5°	159.2
70°	118.6
72.5°	81.0
75°	49.2
77.5°	23.2
80°	5.8
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)