

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205010

Luminaire Tested: **LSR6B30D010BZ EC6B30509040 6LBSCMMS1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205010
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR6B30D010BZ EC6B30509040 6LBCSMMS1
Description: PORTFOLIO 6IN CYLINDER
SHALLOW DISTRIBUTION WITH CAST MATTE METALLIC SILVER TRIM
WATTAGE D010TR-27.4 W DE010-27.95 W D5LT-27.65 W DMX-27.73 W DL2-29.56 W
DL3-29.67 W DLE-29.73 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2637.2 lumens
Efficiency: N/A
Efficacy: 94.2 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205010

CATALOG NUMBER: LSR6B30D010BZ EC6B30509040 6LBCSMMS1

Luminous Intensity Polar Plot





TEST NUMBER: P205010

CATALOG NUMBER: LSR6B30D010BZ EC6B30509040 6LBCSMMS1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	111	107	103	100	108	105	101	98	100	98	95	97	94	92	93	91	90	88			88
2	102	95	89	84	99	93	88	83	90	85	81	86	83	79	83	80	78	76			76
3	94	85	77	72	92	83	76	71	80	74	70	77	73	69	75	71	67	65			65
4	87	76	68	62	84	74	67	61	72	66	61	70	64	60	68	63	59	57			57
5	80	68	60	54	78	67	59	54	65	58	53	63	57	53	61	56	52	50			50
6	74	62	54	48	72	61	53	47	59	52	47	58	51	47	56	51	46	44			44
7	69	56	48	42	67	56	48	42	54	47	42	53	46	42	51	46	41	40			40
8	64	52	44	38	63	51	43	38	50	43	38	48	42	38	47	42	37	36			36
9	60	48	40	35	59	47	40	34	46	39	34	45	39	34	44	38	34	32			32
10	57	44	36	31	55	43	36	31	43	36	31	42	35	31	41	35	31	29			29

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205010

CATALOG NUMBER: LSR6B30D010BZ EC6B30509040 6LBCSMMS1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	114.1	4.3
10°-20°	320.2	12.1
20°-30°	467.7	17.7
30°-40°	535.0	20.3
40°-50°	514.2	19.5
50°-60°	397.0	15.1
60°-70°	221.6	8.4
70°-80°	64.5	2.4
80°-90°	2.8	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	902.1	34.2
0°-40°	1437.1	54.5
0°-60°	2348.3	89.0
0°-90°	2637.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2637.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1211	
5°	1201	114
15°	1136	320
25°	1017	468
35°	856	535
45°	670	514
55°	445	397
65°	222	222
75°	56	64
85°	2	3
90°	0	



TEST NUMBER: P205010

CATALOG NUMBER: LSR6B30D010BZ EC6B30509040 6LBCSMMS1

CANDELA DISTRIBUTION (FULL):

	0°
0°	1211.1
2.5°	1211.1
5°	1200.8
7.5°	1195.7
10°	1178.7
12.5°	1158.2
15°	1136.0
17.5°	1113.8
20°	1081.4
22.5°	1055.8
25°	1016.6
27.5°	977.4
30°	938.2
32.5°	898.9
35°	856.3
37.5°	813.6
40°	764.2
42.5°	719.8
45°	670.4
47.5°	614.1
50°	561.2
52.5°	503.2
55°	445.2
57.5°	385.5
60°	329.2
62.5°	272.9
65°	221.7
67.5°	174.0
70°	129.6
72.5°	90.4
75°	56.3
77.5°	29.0
80°	10.2
82.5°	3.4
85°	1.7
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)