

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204606

Luminaire Tested: **LSR6B40D010BZ EC6B30509024 6LBSMW1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P204606  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSR6B40D010BZ EC6B30509024 6LBSMW1  
Description: PORTFOLIO 6IN CYLINDER  
SHALLOW DISTRIBUTION WITH MATTE WHITE TRIM  
WATTAGE D010TR-43.02 W DE010-42.54 W D5LT-42.539 W DMX-41.87 W DL2-41.57  
W DL3-44.71 W DLE-39.33 W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 3278.8 lumens  
Efficiency: N/A  
Efficacy: 78.4 lumens/watt  
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 41.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P204606

CATALOG NUMBER: LSR6B40D010BZ EC6B30509024 6LBSMW1

### Luminous Intensity Polar Plot





TEST NUMBER: P204606

CATALOG NUMBER: LSR6B40D010BZ EC6B30509024 6LBSMW1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									20									
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																														
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																												
1	110	106	102	99	107	104	100	97	99	97	94	96	93	91	92	90	88	86																												
2	101	93	87	82	98	92	86	81	88	83	79	85	81	77	82	79	76	74																												
3	93	83	75	69	90	81	74	69	78	72	67	76	70	66	73	69	65	63																												
4	85	74	65	59	83	72	65	59	70	63	58	68	62	57	66	61	56	54																												
5	78	66	58	51	76	65	57	51	63	56	51	61	55	50	59	54	49	47																												
6	73	60	51	45	71	59	51	45	57	50	44	55	49	44	54	48	44	42																												
7	67	54	46	40	66	54	46	40	52	45	40	51	44	39	49	43	39	37																												
8	63	50	41	36	61	49	41	36	48	41	35	46	40	35	45	39	35	33																												
9	59	46	38	32	57	45	37	32	44	37	32	43	36	32	42	36	32	30																												
10	55	42	34	29	54	42	34	29	41	34	29	40	33	29	39	33	29	27																												

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P204606

CATALOG NUMBER: LSR6B40D010BZ EC6B30509024 6LBSMW1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	125.2	3.8
10°-20°	356.8	10.9
20°-30°	537.3	16.4
30°-40°	639.4	19.5
40°-50°	638.2	19.5
50°-60°	519.0	15.8
60°-70°	319.3	9.7
70°-80°	123.7	3.8
80°-90°	19.8	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1019.3	31.1
0°-40°	1658.7	50.6
0°-60°	2815.9	85.9
0°-90°	3278.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3278.8	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1321	
5°	1317	125
15°	1267	357
25°	1170	537
35°	1024	639
45°	830	638
55°	581	519
65°	320	319
75°	113	124
85°	16	20
90°	0	



TEST NUMBER: P204606

CATALOG NUMBER: LSR6B40D010BZ EC6B30509024 6LBSMW1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1321.0
2.5°	1323.0
5°	1317.1
7.5°	1309.4
10°	1299.6
12.5°	1282.2
15°	1266.6
17.5°	1243.3
20°	1218.1
22.5°	1194.7
25°	1169.5
27.5°	1134.5
30°	1099.6
32.5°	1066.5
35°	1023.8
37.5°	977.2
40°	934.4
42.5°	882.0
45°	829.5
47.5°	773.2
50°	713.0
52.5°	650.8
55°	580.9
57.5°	512.9
60°	446.8
62.5°	382.7
65°	320.5
67.5°	262.3
70°	207.9
72.5°	157.4
75°	112.7
77.5°	73.8
80°	44.7
82.5°	27.2
85°	15.5
87.5°	7.8
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)