

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203163

Luminaire Tested: **LSR6B40D010BZ EC6B30509024 6LBWMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203163
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR6B40D010BZ EC6B30509024 6LBWMW1
Description: PORTFOLIO 6IN CYLINDER
WIDE DISTRIBUTION WITH MATTE WHITE TRIM
WATTAGE D010TR-43.02 W DE010-42.54 W D5LT-42.539 W DMX-41.87 W DL2-41.57
W DL3-44.71 W DLE-39.33 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2853.4 lumens
Efficiency: N/A
Efficacy: 68.3 lumens/watt
Spacing Criteria (0/90/45): 1.13 / 1.13 / 1.15
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203163

CATALOG NUMBER: LSR6B40D010BZ EC6B30509024 6LBWMW1

Luminous Intensity Polar Plot





TEST NUMBER: P203163

CATALOG NUMBER: LSR6B40D010BZ EC6B30509024 6LBWMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	111	107	104	100	108	105	102	99	101	98	96	97	95	93	93	92	90	88																			
2	103	96	90	86	100	94	89	85	91	86	83	88	84	81	85	82	79	77																			
3	95	86	80	74	93	85	79	74	82	77	72	80	75	71	77	73	70	68																			
4	89	78	71	65	86	77	70	65	75	69	64	72	67	63	70	66	62	60																			
5	82	71	64	58	80	70	63	58	68	62	57	66	61	56	65	60	56	54																			
6	77	65	57	52	75	64	57	52	63	56	51	61	55	51	60	54	50	49																			
7	72	60	52	47	70	59	52	47	58	51	46	56	50	46	55	50	46	44																			
8	67	55	48	42	66	55	47	42	53	47	42	52	46	42	51	46	42	40																			
9	63	51	44	39	62	51	44	39	50	43	39	49	43	38	48	42	38	37																			
10	60	48	40	36	58	47	40	36	46	40	36	45	40	35	45	39	35	34																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203163

CATALOG NUMBER: LSR6B40D010BZ EC6B30509024 6LBWMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	150.9	5.3
10°-20°	423.2	14.8
20°-30°	609.7	21.4
30°-40°	633.1	22.2
40°-50°	468.0	16.4
50°-60°	279.6	9.8
60°-70°	169.9	6.0
70°-80°	93.1	3.3
80°-90°	25.9	0.9
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1183.8	41.5
0°-40°	1816.9	63.7
0°-60°	2564.6	89.9
0°-90°	2853.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2853.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1602	
5°	1592	151
15°	1502	423
25°	1329	610
35°	1021	633
45°	602	468
55°	305	280
65°	170	170
75°	86	93
85°	21	26
90°	0	



TEST NUMBER: P203163

CATALOG NUMBER: LSR6B40D010BZ EC6B30509024 6LBWMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	1602.4
2.5°	1602.4
5°	1592.0
7.5°	1578.1
10°	1557.4
12.5°	1533.1
15°	1502.0
17.5°	1467.4
20°	1432.8
22.5°	1384.3
25°	1329.0
27.5°	1270.1
30°	1194.0
32.5°	1117.8
35°	1020.9
37.5°	920.6
40°	809.8
42.5°	702.5
45°	602.2
47.5°	512.2
50°	432.6
52.5°	363.4
55°	304.6
57.5°	259.6
60°	221.5
62.5°	193.8
65°	169.6
67.5°	148.8
70°	128.1
72.5°	107.3
75°	86.5
77.5°	69.2
80°	51.9
82.5°	38.1
85°	20.8
87.5°	10.4
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)