

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204911

Luminaire Tested: **LSR6B40D010BZ EC6B30508027 6LBCSMB1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P204911  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSR6B40D010BZ EC6B30508027 6LBCSMB1  
Description: PORTFOLIO 6IN CYLINDER  
SHALLOW DISTRIBUTION WITH CAST MATTE BLACK TRIM  
WATTAGE D010TR-43.02 W DE010-42.54 W D5LT-42.539 W DMX-41.87 W DL2-41.57  
W DL3-44.71 W DLE-39.33 W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 3708.7 lumens  
Efficiency: N/A  
Efficacy: 88.7 lumens/watt  
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 41.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P204911

CATALOG NUMBER: LSR6B40D010BZ EC6B30508027 6LBCSMB1

### Luminous Intensity Polar Plot





TEST NUMBER: P204911

CATALOG NUMBER: LSR6B40D010BZ EC6B30508027 6LBCSMB1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	111	107	103	100	108	104	101	98	100	98	95	96	94	92	93	91	90	88																			
2	102	95	89	84	99	93	87	83	89	85	81	86	82	79	83	80	77	75																			
3	93	84	77	71	91	83	76	70	80	74	69	77	72	68	74	70	67	65																			
4	86	75	67	61	84	74	66	61	71	65	60	69	63	59	67	62	58	56																			
5	79	67	59	53	77	66	59	53	64	57	52	62	56	52	61	55	51	49																			
6	74	61	53	47	72	60	52	46	58	51	46	57	50	46	55	50	45	43																			
7	68	55	47	41	67	55	47	41	53	46	41	52	45	41	50	45	40	39																			
8	64	51	43	37	62	50	42	37	49	42	37	48	41	37	46	41	36	35																			
9	60	47	39	33	58	46	39	33	45	38	33	44	38	33	43	37	33	31																			
10	56	43	35	30	55	43	35	30	42	35	30	41	34	30	40	34	30	28																			

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P204911

CATALOG NUMBER: LSR6B40D010BZ EC6B30508027 6LBCSMB1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	148.1	4.0
10°-20°	422.0	11.4
20°-30°	634.4	17.1
30°-40°	752.7	20.3
40°-50°	744.9	20.1
50°-60°	585.1	15.8
60°-70°	328.0	8.8
70°-80°	92.1	2.5
80°-90°	1.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1204.5	32.5
0°-40°	1957.2	52.8
0°-60°	3287.1	88.6
0°-90°	3708.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3708.7	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1566	
5°	1563	148
15°	1497	422
25°	1377	634
35°	1207	753
45°	970	745
55°	659	585
65°	327	328
75°	80	92
85°	0	1
90°	0	



TEST NUMBER: P204911

CATALOG NUMBER: LSR6B40D010BZ EC6B30508027 6LBCSMB1

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	1566.0
2.5°	1560.7
5°	1563.4
7.5°	1550.1
10°	1534.1
12.5°	1515.5
15°	1496.9
17.5°	1473.0
20°	1441.1
22.5°	1409.2
25°	1377.3
27.5°	1342.7
30°	1297.5
32.5°	1252.3
35°	1207.1
37.5°	1153.9
40°	1092.8
42.5°	1034.3
45°	970.5
47.5°	898.7
50°	824.2
52.5°	739.1
55°	659.4
57.5°	569.0
60°	483.9
62.5°	406.8
65°	327.0
67.5°	257.9
70°	191.4
72.5°	130.3
75°	79.8
77.5°	39.9
80°	10.6
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)