

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P202851

Luminaire Tested: **LSR6B40D010BZ EC6B30508035 6LBWWH1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P202851  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSR6B40D010BZ EC6B30508035 6LBWWH1  
Description: PORTFOLIO 6IN CYLINDER  
WIDE DISTRIBUTION WITH WHEAT TRIM  
WATTAGE D010TR-43.02 W DE010-42.54 W D5LT-42.539 W DMX-41.87 W DL2-41.57  
W DL3-44.71 W DLE-39.33 W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 3914.0 lumens  
Efficiency: N/A  
Efficacy: 93.6 lumens/watt  
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.18  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 41.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P202851

CATALOG NUMBER: LSR6B40D010BZ EC6B30508035 6LBWWH1

### Luminous Intensity Polar Plot





TEST NUMBER: P202851

CATALOG NUMBER: LSR6B40D010BZ EC6B30508035 6LBWWH1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	109	107	104	110	107	105	102	103	101	99	99	98	96	96	95	93	92
2	106	100	96	92	104	98	94	91	95	92	89	92	89	87	89	87	85	83
3	99	92	86	81	97	90	85	81	88	83	79	85	81	78	83	80	77	75
4	93	84	78	73	91	83	77	72	81	76	71	79	74	71	77	73	70	68
5	87	77	71	66	85	76	70	65	75	69	65	73	68	64	71	67	63	62
6	82	71	64	59	80	71	64	59	69	63	59	67	62	58	66	61	58	56
7	77	66	59	54	75	65	59	54	64	58	54	63	57	53	61	57	53	51
8	72	61	54	49	71	61	54	49	59	53	49	58	53	49	57	52	49	47
9	68	57	50	45	67	56	50	45	55	49	45	54	49	45	53	48	45	43
10	64	53	46	42	63	53	46	42	52	46	42	51	45	42	50	45	41	40

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P202851

CATALOG NUMBER: LSR6B40D010BZ EC6B30508035 6LBWWH1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	233.7	6.0
10°-20°	694.9	17.8
20°-30°	1046.0	26.7
30°-40°	1069.5	27.3
40°-50°	649.5	16.6
50°-60°	182.9	4.7
60°-70°	27.8	0.7
70°-80°	9.0	0.2
80°-90°	0.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1974.6	50.4
0°-40°	3044.1	77.8
0°-60°	3876.5	99.0
0°-90°	3914.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3914.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2431	
5°	2441	234
15°	2460	695
25°	2284	1046
35°	1734	1070
45°	835	650
55°	182	183
65°	25	28
75°	10	9
85°	0	1
90°	0	



TEST NUMBER: P202851

CATALOG NUMBER: LSR6B40D010BZ EC6B30508035 6LBWWH1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	2431.1
2.5°	2431.1
5°	2440.9
7.5°	2455.6
10°	2455.6
12.5°	2465.5
15°	2460.5
17.5°	2450.7
20°	2416.3
22.5°	2367.2
25°	2283.7
27.5°	2190.4
30°	2062.7
32.5°	1910.5
35°	1733.7
37.5°	1537.2
40°	1311.3
42.5°	1075.6
45°	834.9
47.5°	618.8
50°	437.1
52.5°	294.7
55°	181.7
57.5°	108.0
60°	54.0
62.5°	34.4
65°	24.6
67.5°	19.6
70°	14.7
72.5°	9.8
75°	9.8
77.5°	4.9
80°	4.9
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)